

Est.  
1841

YORK  
ST JOHN  
UNIVERSITY

Schwendel, Arved ORCID logoORCID:  
<https://orcid.org/0000-0003-2937-1748>, Death, Russell G. and Fuller, Ian F. (2009) The assessment of shear stress and bed stability in stream ecology. *Freshwater Biology*, 55. pp. 261-281.

Downloaded from: <https://ray.yorks.ac.uk/id/eprint/3070/>

The version presented here may differ from the published version or version of record. If you intend to cite from the work you are advised to consult the publisher's version:

<https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1365-2427.2009.02293.x>

Research at York St John (RaY) is an institutional repository. It supports the principles of open access by making the research outputs of the University available in digital form. Copyright of the items stored in RaY reside with the authors and/or other copyright owners. Users may access full text items free of charge, and may download a copy for private study or non-commercial research. For further reuse terms, see licence terms governing individual outputs. [Institutional Repository Policy Statement](#)

# RaY

Research at the University of York St John

For more information please contact RaY at [ray@yorks.ac.uk](mailto:ray@yorks.ac.uk)



**The assessment of shear stress and bed stability in stream ecology**

Journal:	<i>Freshwater Biology</i>
Manuscript ID:	FWB-R-Dec-08-0621.R2
Manuscript Type:	Review
Date Submitted by the Author:	
Complete List of Authors:	Schwendel, Arved; Massey University, Institute of Natural Resources - Ecology Death, Russell; Massey University, Institute of Natural Resources - Ecology Fuller, Ian; Massey University, School of People, Environment & Planning - Geography Programme
Keywords:	Community < Level of Organisation, Running water / rivers / streams < Habitat, Ecosystem < Level of Organisation, Benthos < Taxonomic Group / Assemblage, Erosion / sedimentation / landuse < Applied Issues, Geo- and fluvial morphology < Process / Approach / Methods, Hydrology < Process / Approach / Methods



## The assessment of shear stress and bed stability in stream ecology

Arved C. Schwendel, Ecology Group, Institute of Natural Resources, Massey University,  
Private Bag 11222, Palmerston North 4442, New Zealand, Email:

A.C.Schwendel@massey.ac.nz

Russell G. Death, Ecology Group, Institute of Natural Resources, Massey University,  
Palmerston North, New Zealand

Ian C. Fuller, Geography Programme, School of People, Environment & Planning,  
Massey University, Palmerston North

Abbreviated title: The assessment of shear stress and bed stability

Keywords: bedload transport, substratum stability, stream ecology, abrasion, tracer

## Summary

1. Substratum stability and shear stress exerted by flowing water can have a strong influence on the structure of benthic communities. Bed stability can be characterised in a variety of ways, e.g. flow competence, threshold of particle entrainment, measures of erosion and deposition, particle transport distance, abrasion and bedload transport rate. This paper reviews methods for the quantification of bed stability and shear stress in streams and rivers that are relevant for the examination of the relationships between stream biota and bed stability.
2. The most suitable method for a research project depends mainly on the objectives. The targeted group of biota, spatial and temporal scale of investigation, as well as hydraulic conditions and substratum characteristics at the study site(s) determine the choice of a technique for the assessment of bed stability.
3. Indirect measurement of shear stress can be more accurate than calculations based on the DuBoys equation. However, the latter is preferred for reach-wide applications within the limits imposed by hydraulic conditions. The entrainment of the substratum is most effectively assessed using a combination of shear stress and competence equations, but the latter require careful parameterisation. At the patch-scale, direct measurement of entrainment force is a valid alternative.
4. Morphometric budgeting is the most comprehensive and least invasive technique for the assessment of rates of erosion and deposition. The transport of substratum particles is efficiently monitored with *in situ* marked or active tracer particles which allow for rapid and non-invasive identification and high recovery rate. As the assessment of bedload transport rate by formulae can be inaccurate, direct measurement is preferred. However, bedload traps interfere with the substratum and continuity of measurement with samplers is limited. Thus developments in the sector of acoustic and piezoelectric devices offer a potential alternative.
5. The abrasive forces by suspended sediments on stream biota are effectively evaluated with artificial blocks that are fixed on the stream bed. Descriptive surveys that assess bed stability offer an alternative to direct measurement and calculations. They are straightforward and non-invasive but can be observer-biased. If single methods do not provide useful links with biological data this may be improved by the application of a multivariate approach.
6. Many of the methods assessed have not yet been applied in research on benthic communities, but these hydraulic and geomorphologic techniques offer considerable potential for the assessment of bed stability in stream ecology.

## Introduction

Floods are an important controlling force on lotic ecosystems (Death, 2008) and influence the composition of benthic communities (Resh *et al.*, 1988; Reice, Wissmar & Naiman, 1990; Lake, 2000). Most stream ecologists agree that discharges exceeding some threshold act as a disturbance to benthic communities, although determining those values can be problematic (Poff, 1992; Death & Winterbourn, 1994).

Under low water velocity and shear stress sediment is not entrained and the impact on benthic organisms is limited to shear force (drag and lift) exerted by flowing water. This alone may cause the patchy distribution of benthic organisms and can lead to downstream displacement of macrophytes (Biggs *et al.*, 2001), periphyton (Biggs, Smith & Duncan, 1999; Suren & Duncan, 1999) and invertebrates (Lancaster & Hildrew, 1993a; Bond & Downes, 2000; Bond & Downes, 2003). As velocity and shear stress increase, phase-I bedload transport occurs when fine sediments may be winnowed (washed out) and rolled over a mostly stable coarser bed. This can lead to an additional impact on stream biota by abrasion (Downes *et al.*, 1998; Bond & Downes, 2003). At a critical flow velocity, the movement of larger particles is initiated (phase-II bedload transport). This usually involves disruption of any armour layer (see Appendix A for definitions) at the bed surface and can result in patchy areas of scour and deposition (Powell, 1998; Matthaei, Peacock & Townsend, 1999b). In more extreme events, the whole bed may be mobilised, altering the habitat structure dramatically. This can lead to displacement of plants and invertebrates (Giberson & Caissie, 1998; Matthaei, Arbuckle & Townsend, 2000; Bond & Downes, 2003) and mortality of invertebrates crushed by rolling stones. Thus floods which induce bedload transport are often associated with the most dramatic changes in the composition, density and biomass of benthic invertebrate communities (Holomuzki & Biggs, 2000; Death, 2008) and periphyton (Biggs *et al.*, 1999).

To examine the relationship between benthic biota and bed stability it is essential to quantify the latter accurately (Gordon, McMahon & Finlayson, 1992). There have been numerous attempts to do so, but most of the methods developed for stream hydraulics and fluvial geomorphology have yet to be adopted by stream ecologists. Furthermore, recent technological advances (e.g. acoustic and electronic sensors, active tracer particles and topographic survey methods) offer considerable potential for improving the measurement of bed movement for the study of stability-biota relationships.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

This review presents methods that are used to assess different aspects of bed stability at different spatial and temporal scales, including: 1) shear stress, 2) entrainment, 3) erosion and deposition, 4) bedload transport and 5) abrasion. The techniques are evaluated not only for their potential to predict shear force and sediment movement *per se*, but also for their ability to explain biota-substratum stability relations.

### Characteristics of bed stability

#### Shear stress

When stream flow lacks sufficient energy to move bedload (non competent discharges), or where the bed is armoured or substratum particles are locked together (imbricated), the shear stress exerted on benthic biota by increased flows may be sufficient to alter the composition of benthic communities (Lancaster & Hildrew, 1993a; Bond & Downes, 2000; Bond & Downes, 2003). Shear forces exerted on organisms depend on their morphometry as well as kinematic viscosity and fluid velocity. Hence, the measurement of the latter can be used to determine shear stress. However, measurement of the velocity that affects small benthic organisms is difficult due to the steep velocity gradient in the boundary layer. Consequently indirect methods, like exposure to the flow of particles of known weight and/ or size, are employed to estimate the shear stress exerted at the channel bottom.

#### *DuBoys equation*

In stream ecology it is common to use the DuBoys equation (1) to gain an estimate of the mean boundary shear stress  $\tau_o$  at the reach level (e.g. Statzner, Gore & Resh, 1988; Matthaei *et al.*, 1996; Duncan, Suren & Brown, 1999; Matthaei *et al.*, 1999b).

$$\tau_o = \rho_f g R S_f \quad (1)$$

The friction slope  $S_f$  (see Appendix B for symbol annotation) differs from the bed slope  $S_b$  and the water surface slope  $S_w$ , because flow resistance is responsible for energy losses (Robert, 1990).  $S_f$  can be calculated using a backwater calculation if flow data and channel geometry are available. However, the observed differences between  $S_f$  and  $S_w$  are often slight, especially under conditions of high discharge (Powell & Ashworth, 1995; Milan *et al.*, 2001). Thus, the more easily measured  $S_w$  is an acceptable first-order approximation for  $S_f$  (Baker & Ritter, 1975; Lorang & Hauer, 2003). When the width-depth ratio of the channel is high (>16.9 according to Giberson & Caissie, 1998), which is common in coarse bedload transporting streams, mean flow depth  $h$  may be substituted for the hydraulic radius  $R$  (Baker

1  
2 & Ritter, 1975; Powell & Ashworth, 1995; Downes, Glaister & Lake, 1997; Giberson &  
3 Caissie, 1998). The use of local bed slope and depth instead of  $R$  and  $S_f$  in (1) might be  
4 preferable for the estimation of stream stability at the patch-scale, although actual shear stress  
5 is underestimated (Lorang & Hauer, 2003). Furthermore, it should be remembered that fluid  
6 density  $\rho_f$  is usually higher than the  $1000 \text{ kg}\cdot\text{m}^{-3}$  typically used because of suspended  
7 material, particularly during floods (Giberson & Caissie, 1998).

8  
9  
10  
11  
12  
13  
14 The DuBoys equation is strictly applicable only under uniform flow conditions  
15 (implying even bed topography and regular channel geometry) in wide channels ( $W/h > 20$ )  
16 (Gordon *et al.*, 1992; Gore, 1996). Three-dimensional flow effects (Milan *et al.*, 2001),  
17 bedform structures (e.g. pebble clusters and imbrication) (Carson & Griffiths, 1987) and the  
18 exposure to the thalweg (main thread of maximum velocity flow) are not accounted for. The  
19 values derived are high compared with local shear stress calculated from velocity profiles  
20 (Robert, 1990), but tend to underestimate the effective shear force (Carson & Griffiths, 1987).

21  
22  
23  
24  
25  
26  
27 The theoretical assessment of mean boundary shear stress is mostly based on the  
28 DuBoys equation. The choice of the parameters determines scale and accuracy of the  
29 calculation (Table 1). As the flow in natural rivers (especially shallow high gradient boulder-  
30 and gravel-bed rivers) is usually not uniform, the explanatory power of equations assuming  
31 the latter is limited (Campbell & Sidle, 1985). This may be enhanced by the inclusion of  
32 parameters like flow resistance, channel geometry and the energy slope (Lorang & Hauer,  
33 2003). Thus shear stress estimations based on the DuBoys formula apply best under  
34 conditions of increased relative depth ( $R/D_{84} > 4$  (Hey, 1979)), e.g. during high discharges,  
35 when flow is approximately uniform (Bhowmik, 1982; Milan *et al.*, 2001). However, mean  
36 boundary shear stress from the DuBoys equation has been linked with the distribution of  
37 benthic invertebrates in several studies under various discharges (Statzner *et al.*, 1988;  
38 Matthaei *et al.*, 1996). The equation provides a useful tool for reach-wide investigations of  
39 shear stress biota relationships.

#### 40 41 42 43 44 45 46 47 48 49 50 51 *FST-hemispheres*

52  
53 Calibrated FliesswasserStammtisch (FST) hemispheres of different densities offer a measure  
54 of actual near-bed shear stress at a particular point in time (Statzner & Muller, 1989; Statzner,  
55 Kohmann & Hildrew, 1991). Despite some debate about the usefulness of FST-hemispheres  
56 for assessment of near-bed shear stress (Frutiger & Schib, 1993; Statzner, 1993; Dittrich &  
57 Schmedtje, 1995) they performed consistently well as indicators of ecologically relevant  
58 near-bed shear forces in hydraulically rough stream beds (Lancaster & Hildrew, 1993b;  
59  
60



1  
2  
3 Scarsbrook & Townsend, 1993; Dittrich & Schmedtje, 1995; Hardison & Layzer, 2001;  
4 Merigoux & Doledec, 2004). However, Frutiger & Schib (1993) reported that only 50% of  
5 their benthic invertebrate taxa showed a relation between abundance and FST data. Statistical  
6 models based on FST measurements allow long-term characterisation of shear stress  
7 variability (Lamouroux *et al.*, 1992) that can be linked with variation in the density of  
8 invertebrate taxa in different hydraulic microhabitats (Doledec *et al.*, 2007). FST-  
9 hemispheres are a useful tool for investigating the spatial distribution of stream biota at base  
10 flow (Table 1). However, at higher discharges application is limited due to interference from  
11 bedload (impacts from saltating particles) and safety reasons (but see Gore *et al.*, 1994).

### 18 *Near-bed flow velocity*

19  
20  
21 Local shear stress can be estimated from measurements of flow velocity (e.g. single near-bed,  
22 vertical profile). Often a semi-logarithmic relationship between depth and velocity is assumed  
23 which is violated in reaches with high relative roughness (e.g.  $h/D_{84} < 3$  (Bray, 1980)).  
24  
25 Wiberg & Smith (1991) found that local shear stress calculated from depth averaged velocity  
26 derived from a profile was accurate for  $h/D_{84} > 1$ . In comparison, single point near-bed  
27 measurement allows a calculation of shear stress for the widest range of conditions, but is not  
28 as accurate as the depth averaged method. Estimations of boundary shear stress based on the  
29 relation of  $v$  and  $\ln(1-h)$  in velocity profiles (e.g. Bhowmik, 1982) are the least accurate and  
30 apply in the most restricted flow conditions but require no estimate of bed roughness  
31 (Wilcock, 1996).

32  
33  
34  
35  
36  
37  
38  
39  
40 Effenberger *et al.* (2006) found a strong relationship between point measurements of  
41 near-bed flow velocity and the spatial distribution of invertebrates. Death & Winterbourn  
42 (1994) also found a strong positive correlation between the variability of near-bed flow  
43 velocity and the movement of marked stones.

44  
45  
46  
47  
48 Locally, indirect measurement of shear stress can provide more accurate results than the  
49 DuBoys approach. It may also give an indication of the impact of shear stress on stream biota  
50 (Table 1) although the small spatial and temporal extent of the measurements limits the use  
51 for larger reaches and/or long-term studies.

### 56 **Substratum entrainment**

#### 57 *Relationship between substratum grain size and tractive force*

58  
59  
60 The proximal equality between mean boundary shear stress, calculated by the DuBoys



equation, and the maximum diameter of entrained particles (rounded, non-cohesive,  $> 0.05$  m) (Lane, 1955) has been widely exploited to define critical particle size for entrainment (Newbury, 1984; Death & Winterbourn, 1994; Muotka & Virtanen, 1995; Giberson & Caissie, 1998). Even for non-rounded particles comparable relationships have been developed (Newbury, 1984). Although this relationship can provide a good indication of habitat stability amongst sites within a stream (Giberson & Caissie, 1998), it can overestimate particle movement in steep or narrow rivers ( $W/h < 16.5$ ) as well as underestimate it in wide and shallow channels ( $W/h > 36.9$ ) (Hallisey & Belt, 1996). This approach is subject to the same constraints as the DuBoys equation and does not account for potential equal mobility due to hiding and protrusion of particles. Thus the applicability of this concept is constrained to rivers with a high relative depth ( $h \gg D_{50}$ ) (approx. 6-7 (Newbury, 1984),  $> 10$  (Duncan *et al.*, 1999)) and bed slopes less than 0.01, conditions which are more likely to be met in lowland rivers.

Not surprisingly, therefore, several authors found no significant relationship with other measures of bed stability when they applied this approach in steep and shallow streams (Death & Winterbourn, 1994; Duncan *et al.*, 1999). In contrast Cobb, Galloway & Flannagan (1992), Scarsbrook & Townsend (1993) and Muotka & Virtanen (1995) found a link between critical tractive force and the distribution of invertebrates and bryophytes. However, the relationship between tractive force and critical particle diameter cannot predict entrainment of the substratum consistently and applies in a limited range of rivers with gentle slope and high relative depth.

#### *Shields equation*

The Shields equation (2) (Shields, 1936) relates boundary shear stress to particle entrainment. It estimates the critical shear stress for a substratum grain size  $D_i$  at the point of incipient motion.

$$\tau_{\text{crit}} = \theta_{\text{crit}} (\gamma_s - \gamma_f) D_i \quad (2)$$

The Shields coefficient  $\theta_{\text{crit}}$  is a non-dimensional variable dependent on particle shape, substratum particle size distribution, exposure and other packing factors (Lorang & Hauer, 2003). It reaches a constant value for non-cohesive materials larger than 6 mm (Lorang & Hauer, 2003) for hydraulically rough beds (boundary  $Re > 100$ ).  $\theta_{\text{crit}}$  varies coarsely between 0.02 and 0.08, but more extreme values have been reported (Ashworth & Ferguson, 1989; Buffington & Montgomery, 1997; Shvidchenko, Pender & Hoey, 2001). Increasing channel slope (related to relative flow depth ( $h/D_{50}$ )), decreasing relative size ( $D_i/D_{50}$ ) and substratum

heterogeneity (size distribution) increases the Shields coefficient systematically (Bathurst, Graf & Cao, 1987; Buffington & Montgomery, 1997; Shvidchenko *et al.*, 2001). Furthermore, the definition of incipient motion (e.g. reference- or visual observation-based), grain shape, orientation, hiding effects (e.g. sheltering of smaller particles by larger), as well as discharge and bank vegetation influence  $\theta_{crit}$  (Andrews, 1984). Values for  $\theta_{crit}$  derived from visual-based studies (typically around 0.045) are recommended for analyses of incipient motion in discrete bed surface patches. In contrast, the usually higher reference-based  $\theta_{crit}$  may give a better estimate of entrainment on a reach-average level because of its derivation from bedload transport measures and thus the integration of differential bed patch mobility (Buffington & Montgomery, 1997). Compared with the original Shields coefficient of 0.06, in gravel bed streams with a heterogeneous substratum, a lower  $\theta_{crit}$  is expected, for instance down to 0.02 in high gradient rivers ( $S_w > 0.002$ ), where  $D_{Max}/D_{50} > 22$  (Lorang & Hauer, 2003) and the effects of form roughness and form drag resistance are considerable. A value of 0.045 for  $\theta_{crit}$  has been used in many studies and is widely accepted for beds with coarse particles and high boundary Reynolds numbers (Miller, McCave & Komar, 1977; Yalin & Karahan, 1979; Komar, 1989; Duncan *et al.*, 1999).

There have been several attempts to improve the Shields equation and to widen its range of use (e.g. Komar, 1987; Thompson & Croke, 2008). Formulae such as Equation (3) incorporate the effects of hiding and heterogeneous beds in the Shields equation (Komar, 1989):

$$\tau_{crit} = 0.0045 (\gamma_s - \gamma_f) D_{50}^{0.65} D_i^{0.35} \quad (3).$$

Duncan *et al.* (1999) also applied corrections to allow for small relative depths ( $h/D < 2.5$ ) and high water surface slopes. Thompson & Croke (2008) incorporated the effects of bed form, microtopography and bed packing into the Shields equation. Lorang & Hauer (2003) found that critical shear stress calculated with a modified Shields equation overestimated the actual value for large cobble- and boulder-bed rivers by as much as an order of magnitude.

Andrews (1983) (cf. Parker, Klingeman & McLean, 1982) proposed the following relationship to calculate  $\theta_{crit}$  for  $0.3 < D_{isurface}/D_{50subsurface} < 4.2$ :

$$\theta_{crit} = 0.0834 (D_{isurface}/D_{50subsurface})^{-0.872} \quad (4).$$

This highlights the fact that critical shear stress is influenced more by relative grain size than absolute grain size (Ferguson, 1994; Shvidchenko *et al.*, 2001). With the typical ratio of  $D_{50surface}/D_{50subsurface} = 2.5$  for gravel bed rivers (Parker *et al.*, 1982)  $\theta_{crit}$  can be estimated. However, in other studies the value for the first factor in (4) lies between 0.019 and 0.087,

1  
2 whilst the exponent ranges from -0.32 to -1.25 (Buffington & Montgomery, 1997) and the  
3 values differ between riffles and pools (Sear, 1996).  
4  
5

6  
7 A comparison between mean boundary shear stress (1) and critical shear stress for a  
8 particular grain size has been used to indicate zones of entrainment (Milan *et al.*, 2001),  
9 calculate the critical size of substratum particles moved (Duncan *et al.*, 1999) and define  
10 critical depth (Fuller *et al.*, 2002). Predictions of entrainment were well correlated with  
11 measurements of morphological change in most areas of a gravel bed stream (Milan *et al.*,  
12 2001) and entrainment of *in situ* tagged particles (Biggs *et al.*, 2001). Bed stability  
13 measurements derived from a combination of (1) and (3) showed a strong relationship with  
14 the composition of bryophyte communities (Duncan *et al.*, 1999) and periphyton biomass  
15 (Biggs *et al.*, 2001) (Table 2).  
16  
17

18  
19 Given the difficulties of selecting the most suitable parameters for empirical equations  
20 or the Shields coefficient, the calculation of the critical shear stress for entrainment is not  
21 straightforward, especially when a wide range of streams is being examined. However, for  
22 reach-scale investigations of the relationship between biota and bed stability a combination of  
23 the DuBoys formula and an advanced Shields equation (e.g. Duncan *et al.* 1999) may be  
24 useful.  
25  
26

#### 27 28 29 30 31 32 33 34 *Empirical equations of critical shear stress*

35  
36 Several studies have produced empirical entrainment equations of the type  $\tau_{crit} = a D^b$   
37 (Thompson & Croke, 2008), where a and b range from 26.6 to 110 and 0.38 to 1.21  
38 respectively. The large range in parameter values is due to the difference in substratum  
39 assemblage between sites and differing methods used to define parameters (Lorang & Hauer,  
40 2003). These empirical entrainment equations are thus too stream-specific to allow a general  
41 application of this approach.  
42  
43

#### 44 45 46 47 *Spring balance*

48  
49 Downes *et al.* (1997) used spring balances to measure the force necessary to initiate motion  
50 of particles in streams. This cannot be related directly to the critical shear stress but high  
51 forces will generally equate with high shear stresses as long as selective entrainment occurs  
52 (Downes *et al.*, 1997). This is a labour intensive methodology for reach-scale studies and the  
53 choice of particles can be subjective, but it will reflect actual shear stress to entrain particles  
54 better than indirect measurements.  
55  
56  
57  
58  
59  
60

## Erosion and deposition

### *Scour chains and other buried devices*

In both ecology and hydrology the deployment of metal scour chains is a common method for measuring scour and deposition of bed materials (Laronne & Duncan, 1992; Laronne *et al.*, 1992; Palmer, Bely & Berg, 1992; Matthaei *et al.*, 1999b; Matthaei, Guggelberger & Huber, 2003; Effenberger *et al.*, 2006). It allows quantification of the height of fill and the depth of scour with an accuracy ranging from  $<D_{25}$  to  $D_{84}$  (Laronne *et al.*, 1994; Matthaei *et al.*, 2003) on a patch-scale systematic grid. Installation is relatively rapid (33 chains per person per day (Matthaei *et al.*, 1999b)) and causes little damage to sediment structure. Effenberger *et al.* (2006) observed no long-term effects on the invertebrate community. The chains proved to be resistant to dislocation and can be relocated after floods with the help of coloured ropes or magnetic tracers. However, the assessment of temporal variation of scour and fill during bed moving events is limited and relocation is required after each event that is likely to result in substratum movement (Laronne *et al.*, 1994). As (phase-I) bedload transport occurs in patches in gravel bed rivers the suggested resolution of measurement is higher than one observation per square metre (Matthaei *et al.*, 1999b; Laronne, Garcia & Reid, 2001).

Scour chains were employed for the identification of stable bed patches which can serve as local refugia for benthic organisms during floods (Matthaei *et al.*, 1999b). Measures of scour and fill using scour chains have been related to density and vertical distribution of invertebrates (Palmer *et al.*, 1992; Effenberger *et al.*, 2006) as well as to the spatial distribution of benthic algae (Matthaei *et al.*, 2003) (Table 3).

Alternatively, metal scour plates, buried at fixed depths can serve as measurement of scour depth and in sandy streams columns of dyed sand inserted in the top layer of the bed can replace scour chains (Palmer *et al.*, 1992). Wilcock (1997) measured the depth of entrainment with buried painted gravels. But both installation and retrieval require a disturbance of the substratum. Hence these methods are not appropriate for studies targeting benthic biota or for armoured and imbricated streambeds. Pressure pillows inserted into the surface of an artificial stream bed were used by Kurashige (2002) to measure sedimentation rates continuously but the construction was susceptible to damage during high bedload discharges.

### *Morphometric sediment budget models*

Movement of the substratum is reflected in changes of the morphology of the channel (Leopold, 1992). These changes can be assessed with repeated airborne surveys using digital

1  
2  
3 photogrammetry or laser altimetry (e.g. Lane, 2001; Westaway, Lane & Hicks, 2001) or  
4 ground surveys employing tacheometry or photogrammetry (e.g. Ferguson & Ashworth, 1992;  
5 Lane, Chandler & Richards, 1994; Fuller *et al.*, 2002; Heritage & Milan, 2004).  
6  
7

8  
9 Ground surveys have been conducted with a theodolite-EDM system (Chappell *et al.*,  
10 2003; Fuller, Large & Milan, 2003b; Fuller *et al.*, 2005) but more recently also with Real  
11 Time Kinematic differential-GPS (RTK-dGPS) (Brasington, Rumsby & McVey, 2000; Fuller  
12 & Hutchinson, 2007). The difference in altitude of cross-sections or digital elevation models  
13 (DEM) between surveys is used to determine areas of quantified deposition or erosion  
14 (DEM) between surveys is used to determine areas of quantified deposition or erosion  
15 (Brasington *et al.*, 2000; Brewer & Passmore, 2002). The calculation with DEMs is  
16 preferable because sediment budgets derived from planform and cross-section measurement  
17 underestimate the magnitude of volumetric change compared with DEM subtraction, nor do  
18 they permit identification of the spatial pattern of volumetric change (Fuller *et al.*, 2003a).  
19 Altitude measurements with RTK-dGPS or a theodolite-EDM system are, within the limits  
20 imposed by surface roughness (e.g.  $D_{50}$ ) highly accurate and more than 2000 points with high  
21 spatial resolution can be obtained per day (Brasington *et al.*, 2000). The use of a GPS system  
22 is, however, limited at closed canopy sites and in deep valleys where satellite reception is  
23 critical.  
24  
25  
26  
27  
28  
29  
30  
31  
32

33  
34 Brasington, Langham & Rumsby (2003) indicate that ground surveys are much more  
35 precise than remote survey methods (especially at submerged zones; cf. Westaway, Lane &  
36 Hicks, 2000) and thus preferable for morphometric budgeting. However, for very wide river  
37 beds or reaches of more than a few hundred metres in length, the use of photogrammetry  
38 should be considered (Lane, Westaway & Hicks, 2003).  
39  
40  
41  
42

43  
44 Morphometric budgeting has the advantage over scour chains to be less invasive and  
45 the ability to monitor an entire reach. However, scour chains may integrate effects of scour-  
46 fill compensation during single events. Both techniques give a lower bound estimate of the  
47 sediment flux because they do not account for substratum that is transported completely  
48 through the reach (Fuller *et al.*, 2003a). According to Martin & Church (1995) the  
49 morphometric approach provides information of a quality comparable or superior to that of  
50 direct measurements of transport, yet requires less field effort. Its application is restricted to  
51 gravel- and cobble-bed rivers. To the best of our knowledge these measures have not been  
52 used in connection with biological data.  
53  
54  
55  
56  
57  
58  
59  
60

## Bed load transport

Bedload is the sediment component that moves downstream by rolling or saltation. In rivers and streams where hydraulic conditions are generally unsteady (Lisle *et al.*, 2000) and spatial substratum grain size variability is high (Dollar, 2002), transport rate is highly variable in space and time (Gomez, 1991; Batalla, 1997; Ferguson, 2003; Vericat & Batalla, 2007). Bedload discharge also depends on the supply of sediments within the catchment and lateral and longitudinal connectivity of the river (Dietrich *et al.*, 1989; Hooke, 2003; Fryirs *et al.*, 2007). The transport of substratum can be expressed as volumetric change in sediment budgets, transport rate at a point, cross-sectional discharge or distance travelled by individual particles. Techniques for measuring bedload transport are ideally non-intrusive, flexible and representative for different types of transport (Ergenzinger & de Jong, 2003). To date most stream ecologists have only been interested in qualitative measures of bed stability. At the single particle-scale, qualitative assessment might be sufficient, but for whole reaches bedload transport occurs on a continuous graduation. For stream ecologists, quantitative measures of bedload transport can act as a superior indicator for the level of bed stability, particularly if only partial mobilisation of the bed occurs.

### *Tracer particles*

Tracers are well suited for the stochastic and spatially variable nature of bedload transport because they reflect the movement of individual particles of known characteristics (Wilcock, 1997). Marked or tagged natural particles and artificial tracers are used to assess step length of movement (e.g. Habersack, 2001), proportion of the bed surface entrained (e.g. Laronne & Duncan, 1992), transport behaviour (e.g. Gottesfeld & Tunnicliffe, 2003) and transport rate (e.g. Ergenzinger & Conrady, 1982), or as an indicator of bed stability (e.g. Death & Winterbourn, 1994). Further they could facilitate the measurement of recolonisation periods of individual particles.

Stones coated with ordinary paint or fluorescent dye placed on the riverbed are often employed by ecologists and hydrologists (Death & Winterbourn, 1994; Townsend, Scarsbrook & Doledec, 1997; Ferguson & Wathen, 1998; Death, 2002; Ergenzinger & de Jong, 2003; Death & Zimmermann, 2005), but they have the disadvantage of a low recovery rate due to burial (Table 4). To overcome this, metal bars (Laronne *et al.*, 1992; Schmidt & Ergenzinger, 1992) or magnets (Hassan, Church & Schick, 1991; Laronne & Duncan, 1992; Bunte, 1996; Ferguson & Wathen, 1998) can be inserted into the particles and they are detected using a metal detector or a magnetometer respectively. Magnetic tracers usually



1  
2  
3 have a larger detection range (McEwan, Habersack & Heald, 2001) than metal tracers. An  
4 easier but less durable alternative to the insertion of metal is the wrapping of stones with  
5 aluminium foil (Sear *et al.*, 2003). The transport rate and transport behaviour of particles  
6 marked with magnets or stones containing magnetic minerals can be monitored with a bar  
7 equipped with electromagnetic coils across the stream (Ergenzinger, 1985; Carling *et al.*,  
8 1998; Froehlich, 2003) or with a longitudinal line of “Bed Movement Detectors” (Gottesfeld  
9 & Tunnicliffe, 2003). The overpassing of a magnetic particle induces an electric signal which  
10 is stored with high temporal resolution. The calculation of bedload discharge is possible using  
11 dispersion models (Sear *et al.*, 2000b).  
12  
13  
14  
15  
16  
17  
18

19 Marking of tracer particles has been further advanced via insertion of radio transmitters  
20 into a particle. A signal is transmitted either continuously, at a programmed interval or when  
21 the particle is turned 180° (Ergenzinger, Schmidt & Busskamp, 1989; Schmidt & Ergenzinger,  
22 1992; Busskamp & Hasholt, 1996; Habersack, 2001). The tagged stones can be tracked from  
23 the banks with a set of antennae but application is restricted to shallow water and low  
24 conductivity (Ergenzinger & de Jong, 2003). Battery capacity (size) is a trade-off between  
25 life span and lower size boundary of particles (Habersack, 2003). These tags enable the  
26 monitoring of step length and transport behaviour as well as initiation of motion.  
27  
28  
29  
30  
31  
32  
33

34 Radioactive tracers (e.g.  $^{137}\text{Cs}$ ) are an alternative to tags because they do not change  
35 density or centre of gravity (e.g. Bartnik, Madeyski & Michalik, 1992). However, they are no  
36 longer widely applied due to environmental issues (Ergenzinger & de Jong, 2003). The  
37 employment of tracers of differing lithology from the natural substratum (Mosley, 1978;  
38 Kondolf & Matthews, 1986) provides an effective and easy measure for event-based  
39 distribution of transport length, although recovery rate is low.  
40  
41  
42  
43  
44

45 For the *in situ* marking of substratum particles Downes *et al.* (1998) and Matthaei,  
46 Peacock & Townsend (1999a) used chisels and drills with long drill bit extensions, but  
47 relocation is difficult and embeddedness may be disturbed during the marking process. Thus  
48 this method is more suitable for the qualitative measurement of entrainment. Barquin &  
49 Death (2006) used dyed quick curing concrete mix to mark embedded stones.  
50  
51  
52  
53

54 Artificial stones provide an alternative to natural particles and also give the opportunity  
55 to examine the influence of shape on transport length (Schmidt & Ergenzinger, 1992). The  
56 use of cast aluminium forms avoids the insertion of metal bars in pebbles (Sear *et al.*, 2003).  
57 The collection of complex information about particle transport is also possible with artificial  
58  
59  
60



1  
2  
3 boulders like the DUMPLING (Ergenzinger & de Jong, 2003), although its size and weight  
4 restricts its application to bouldery streams.  
5

6  
7 The measurement of bedload transport with tracers provides comparable results to  
8 direct measures but requires less effort and avoids large-scale intervention in the stream bed.  
9 For low transport rates, tracers are likely to be more accurate (Wilcock, 1997). However, the  
10 dominating influence of bed structure and channel morphology on the distribution of tracer  
11 stones and the weak relationship with stream power (Kondolf & Matthews, 1986; Hassan,  
12 Church & Ashworth, 1992) suggests that short-term studies with tracers are not sufficient to  
13 compute rates of bedload transport. In contrast, shorter-term studies are more suitable for  
14 investigating the movement of surface particles because the transport rate of tracer particles  
15 decreases due to vertical mixing (burial) and storage in less active zones of the system (e.g.  
16 floodplain, bars) (Ferguson *et al.*, 2002). If particles have to be removed from the stream for  
17 marking, bed structures and imbrication are destroyed and tracer particles placed on the bed  
18 surface may not represent the size characteristics of the substratum (Downes *et al.*, 1998;  
19 Biggs *et al.*, 1999). Longer-term studies can account for this, but they do not provide  
20 information about the frequency and magnitude of single disturbance events. The subjective  
21 choice and the shape of particles, as well as their number, may bias the results of tracer  
22 experiments (Schmidt & Gintz, 1995; Duncan *et al.*, 1999; Warburton & Demir, 2000;  
23 Ferguson & Hoey, 2002).  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36

37 Nevertheless, a stability index derived from tracer experiments showed a strong  
38 negative relationship with invertebrate diversity and periphyton biomass (Death &  
39 Winterbourn, 1995; Death, 2002; Death & Zimmermann, 2005) (Table 4). *In situ* marked  
40 stones were also used to identify stable stones that can serve as refugia during floods  
41 (Matthaei *et al.*, 2000). They relate the shear forces to the local substratum and consequently  
42 give a better estimate of bed stability than unembedded tracers (Downes *et al.*, 1998;  
43 Matthaei *et al.*, 1999a). In combination with a non-invasive detection technique, *in situ*  
44 marked particles may be highly appropriate for ecological studies. Along with the objectives  
45 of a study, selection of an optimal tracer technique should consider representation of the  
46 substratum, tracer recoverability, longevity, durability, possibility of explicit identification of  
47 particles as well as labour and cost efficiency (Sear *et al.*, 2000b).  
48  
49  
50  
51  
52  
53  
54  
55

#### 56 *Bedload transport sampler and traps*

57  
58 The rate of bedload transport can be assessed with samplers and traps at various scales  
59 (Table 5). The most common handheld bedload transport samplers are of the pressure-  
60

1  
2  
3 difference type (Helley-Smith-, VUV- and Arnhem sampler) with orifices up to 0.05 m<sup>2</sup>  
4 (Leopold, 1992; Hoey, Cudden & Shvidchenko, 2001; Hardardottir & Snorrason, 2003).  
5  
6 Their sampling efficiency usually varies between 30% and 70%, but can be up to 100%  
7 (Helley-Smith sampler) (Gomez, 1991). A common constraint of these samplers is that the  
8 opening area needs calibration for hydraulic and substratum conditions (Gomez, 1991) but,  
9  
10 much more critically, the sampling scheme should be sufficient to account for the cross-  
11 sectional substratum variability of the reach and the temporal variability in bedload transport  
12 (Ergenzinger & de Jong, 2003). This requires adjustment of the sampling period and may  
13 result in large sampling efforts in wide rivers. Therefore, predictions of bedload transport  
14 based on sampler measurements are often not very accurate (uncertainty of  $\pm 50\%$ ) (Wilcock,  
15 2001). In conditions encountered in mountain streams (e.g. local high flow velocities and  
16 high surface roughness) bedload transport samplers are less applicable (Mizuyama, Fujita &  
17 Nonaka, 2003). Here portable net traps fixed to platforms on the stream bed may be used,  
18 delivering similar results to pit traps (Wilcock, 2001; Bunte & Abt, 2003; Bunte *et al.*, 2004).  
19  
20 Bedload samplers are not frequently employed by stream ecologists perhaps because of the  
21 mentioned constraints and inaccuracy. However, for small-scale, event-based studies they  
22 constitute a potentially valid option for direct measurement of bedload transport rate.  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32

33 Slot traps of various dimensions, inserted into the river bed, are used in many parts of  
34 the world (Salehi, Lagace & Pesant, 1997; Martin-Vide *et al.*, 1999; Hassan & Church, 2001;  
35 Sear *et al.*, 2003; Bond, 2004). They range from small sized pit traps, without continuous  
36 measurement, to Birkbeck samplers and large, stream-wide constructions for continuous  
37 monitoring. The latter is achieved with the employment of a weighing device (pressure  
38 cushion, load cell) below the sampling box or outside the channel (vortex tube, pump,  
39 conveyor belt) (Gomez, 1991; Sear *et al.*, 2000a; Ergenzinger & de Jong, 2003; Sear, 2003).  
40 Load cell systems are more reliable than pressure cushion devices because they are less  
41 susceptible to damage (e.g. puncture of pressure pillows) (Lewis, 1991). Smaller pit traps  
42 may fill rapidly during large events but are generally more accurate than handheld bedload  
43 transport samplers (Wilcock, 2001). Sampling efficiency for pit traps is up to 100%,  
44 decreasing with increasing fill (Laronne *et al.*, 2003). In particular at base flow, bedload  
45 transport traps may also sample suspended sediments (Batalla, 1997). The installation and  
46 maintenance of a bedload trap is expensive and involves a serious disturbance of the stream  
47 bed and biota. For this reason, bedload traps have not been used for investigations of benthic  
48 biota but for long-term projects they offer a useful tool for the assessment of ecologically  
49 relevant bedload discharge. As an alternative, monitoring of sediment volume accumulated in  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

1  
2  
3 natural traps (basins), reservoirs or retention and diversion devices provides an opportunity to  
4 assess bedload transport rate, but calibration to exclude suspended sediments is difficult  
5  
6 (Gomez, 1991).  
7

#### 8 *Acoustic sensors*

9  
10 Acoustic sensors can be used to assess bedload transport intensity and the onset and cessation  
11 of movement (Ergenzinger & de Jong, 2003). In addition, estimates of transport rate using  
12 acoustic energy and estimates of transported particle size using the emitted frequency can be  
13 obtained (Bogen & Moen, 2003; Downing *et al.*, 2003; Froehlich, 2003; Mizuyama *et al.*,  
14 2003). Hydrophones must be calibrated against actual bedload samples at each site. The  
15 sensor consists of a plate fixed horizontally on the bed (Bogen & Moen, 2003), a vertical  
16 pressure plate (Downing *et al.*, 2003) or horizontal steel pipes across the stream bed  
17 (Froehlich, 2003; Mizuyama *et al.*, 2003). Calibration limits the application at numerous sites,  
18 but the accuracy can be similar to a bedload trap. Acoustic Doppler Current Profiling (ADCP)  
19 allows the combined measurement of multi dimensional flow and velocity of bedload and  
20 suspended load (Rennie & Millar, 2004). Limitations of this technique include problems with  
21 the differentiation between near-bed suspension, bedload and fine grained bottom sediments  
22 as well as varying sensitivity to different particle sizes (Kostaschuk *et al.*, 2005).  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33

#### 34 *Other sensors*

35  
36 Richardson, Benson & Carling (2003) presented an electronic sensor that allows detection of  
37 the momentum of impacting particles in bedrock channels. It gives a relative measure of  
38 bedload transport but needs to be calibrated. The latter can create some difficulties because  
39 the sensor measures a combination of grain mass and speed.  
40  
41  
42  
43

44 The piezoelectric bedload impact sensor employed by Rickenmann & McArdeU (2007)  
45 can measure impacts of transported grains larger than 10 – 30 mm. These sensors are placed  
46 in an array over the whole stream width in a concrete bar. The measure is a reliable and  
47 continuous indicator of total bedload transport, but it needs to be calibrated and has limited  
48 accuracy for single events or small bedload volumes. Further it gives no information about  
49 the grain size distribution of the overpassing sediments (Rickenmann & McArdeU, 2007).  
50  
51  
52  
53  
54

#### 55 *Bedload transport formulae*

56  
57 Bedload transport formulae (e.g. Schoklitsch-type equation (5)) are generally based on four  
58 principal approaches: shear stress, stream discharge, stream power and a stochastic function  
59 for sediment transport (Gomez & Church, 1989).  
60

$$q_b = X' S_f (q - q_{cr}) \quad (5)$$

In this example, bedload discharge  $q_b$  depends on excess water discharge and a sediment coefficient  $X'$ . Most bedload transport formulae originate from physical principles but their precision has been improved by the use of empirical datasets from flumes and streams. The formulae are consistent in that they employ in most instances the same hydraulic parameters (energy gradient, flow velocity, depth and discharge) which are in part intercorrelated (Gomez & Church, 1989; Martin & Church, 2000). Most formulae are well suited and parameterised for the dataset of their development, but fail when applied to other conditions (Knighton, 2008). They are based on limited basic assumptions which vary between streams and even within streams (e.g. selective entrainment). Characteristics like armouring, exposure to flow, equal mobility, variable sediment supply and pulsing cannot be fully accounted for, although some approaches try to incorporate these points (Parker, 1990; Duan & Scott, 2007; Thompson & Croke, 2008). Furthermore, the spatial variability within a stream is ignored because of the one-dimensional nature of the formulae (Hoey *et al.*, 2001; Ferguson, 2003; Martin & Ham, 2005). The result of comparative studies with bedload samplers/ traps (Gomez & Church, 1989; Batalla, 1997; Martin-Vide *et al.*, 1999; Habersack & Laronne, 2002; Barry, 2004) and morphologic budgeting (Martin & Ham, 2005) show clearly that bedload transport formulae perform inconsistently (but see Bartnik *et al.*, 1992). Thus, bedload transport formulae need to be carefully selected according to the conditions for which they were developed, for instance turbulent and shallow mountain streams require other types of models than gravel-bed rivers (Biggs *et al.*, 2001; Mizuyama *et al.*, 2003; Ancy *et al.*, 2008). Additionally, empirical parameters and the entrainment threshold have to be determined to suit a new dataset, which is a difficult task (Wilcock, 2001; Habersack & Laronne, 2002). Thus the application of direct measurements of bedload transport is preferable to the use of bedload transport formulae (Gomez, 1991; Laronne *et al.*, 1992).

### **Abrasion by suspended sediments**

Abrasion is an often neglected form of disturbance which can affect benthic flora and fauna. At normal flows the stream biota may be subjected to constant *in situ* abrasion by small suspended particles, which may represent a significant disturbance at higher discharges (Biggs, 1996; Peterson, 1996). It is unclear if sandblasting affects invertebrates (Rosenberg & Wiens, 1978; Culp, Wrona & Davies, 1986; Bond & Downes, 2003) but the effect on benthic algae is clearly recognised (Biggs *et al.*, 1999; Webb *et al.*, 2006).

1  
2  
3 The exposure of natural or artificial tracers to abrasion is an obvious opportunity for  
4 quantification (Table 6). The use of natural rocks that are cut in cubes or artificial blocks  
5 improves the visual monitoring of abrasion because the loss of edges and corners is simply  
6 detected. Furthermore, impact marks on the cube faces are subject to easy distinction and aide  
7 the interpretation of bedload moving events (Brewer, Leeks & Lewin, 1992). Blocks that are  
8 of the same lithology as the river sediments have the advantage that they provide a better  
9 estimation of the actual abrasion in the channel. However, for the quantification of the impact  
10 on biota a measure of relative abrasion is sufficient. Thus ecologists prefer to use artificial  
11 tracers, like autoclaved lightweight aerated concrete blocks (Webb *et al.*, 2006). The latter  
12 have standardised material properties and abrade consistently proportional to the physical  
13 work performed on their surface. Moreover the abrasion rate is high enough to allow short  
14 deployment times (e.g. 2 months) which minimises mass loss by dissolution. Abrasion blocks  
15 need to be protected from the impact of bedload transport to gain a pure measure of abrasion  
16 by suspended particles. There is also the choice between blocks fixed on the stream bed or on  
17 bedrock, semi-mobile tethered blocks as well as loose tracer particles of known weight and  
18 size (Stott & Sawyer, 2000). For measurements relevant to stream invertebrates or periphyton  
19 it is preferable to place the blocks on the stream bed. Although fixed or tethered blocks may  
20 split and get lost or buried by sediments, the recovery rate can be high (Brewer *et al.*, 1992).  
21 These methods do not allow distinction between effects of sandblasting, overpassing bed  
22 materials and the physical impingement of fast flowing water. However, the practical  
23 consequences for ecologists are small because, in the field, biota are usually exposed to a  
24 combination of these effects (Webb *et al.*, 2006).  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41

42 Abrasion coefficients derived from laboratory experiments are an easy alternative to  
43 field measurements but they generally underestimate the actual abrasion in rivers (Lewin &  
44 Brewer, 2002). Sklar & Dietrich (2004) presented a model to predict bedrock abrasion by  
45 saltating particles but it has not yet been applied in context with stream biota.  
46  
47  
48  
49  
50  
51

## 52 **Descriptive surveys of substratum stability and multivariate approaches**

### 53 *Pfankuch Stability Index*

54  
55  
56 The Pfankuch Stability Index is a qualitative measure that describes the probability of  
57 occurrence of substratum-moving discharges (Pfankuch, 1975). It consists of 15 variables  
58 representing properties of the upper and lower banks and the stream bed. Despite its  
59 subjectivity it shows a strong positive relation with the entrainment of painted stones  
60

(Townsend *et al.*, 1997), but not when the painted stones are used as an indicator of tractive force over time (Death & Winterbourn, 1994). If just the stream bottom component of the Pfankuch Index is employed, the relationship with other stability measures is considerably higher (Death & Winterbourn, 1994; McIntosh, 2000) and the assessment of stability at finer spatial scales might be possible (Winterbourn & Collier, 1987).

Descriptive approaches for the assessment of stream bed stability provide an easily applicable tool which has been widely exploited for investigations of biota in streams. Their major problem is the propensity to be observer-biased (Duncan *et al.*, 1999). Additionally, large temporal variation in scores can occur between surveys of the same reach by the same observer (A. C. Schwendel, unpublished data). Nevertheless, relations between bed stability assessed with the stream bed component of the Pfankuch Index and biological data have been established (Table 7).

#### *Multivariate approaches*

Approaches that combine more than one measure of bed stability can have a stronger relationship with biological data because they can incorporate different aspects of substratum stability. Death & Winterbourn (1994) showed that a multivariate instability score consisting of hydraulic parameters (patch-scale), the movement of painted stones, water temperature and the bottom component of the Pfankuch index (reach-scale) had a stronger positive linear relationship with invertebrate species richness than with any of the constituent single variables.

#### **Conclusions**

The composition of benthic communities is a function of habitat and biotic interactions. Habitat stability in rivers is primarily determined by the forces of flowing water exerted on biota and substratum. Hence measurement of shear stress and substratum stability can indicate the distribution of benthic stream organisms, but they differ in precision and the aspect of bed stability they describe. Clearly there is no single technique suitable for all applications. Thus the selection of an appropriate method is subject to: (1) targeted fauna (mobility and range of activity), (2) spatial and (3) temporal scale of investigation (flood event-based or long-term), (4) hydraulic and (5) substratum conditions, and (6) research question of the study (e.g. range of flow, aspect of bed stability).



1  
2  
3 Most of the methods presented have been developed for research into stream hydraulics  
4 and fluvial geomorphology. Despite recent technological advances and development of new  
5 techniques only a few of them have been applied in ecological studies. Given the importance  
6 of bed stability for the biota of many streams and rivers and the multitude of ways to  
7 characterise that stability, we would like to encourage stream ecologists to consider also the  
8 potential of alternative techniques highlighted in this review for examining the links between  
9 stream stability and biota.  
10  
11  
12  
13  
14  
15  
16  
17

### 18 **Acknowledgments**

19 We thank Alan Hildrew, Bernhard Statzner and an anonymous reviewer for their helpful  
20 comments on earlier versions of this manuscript.  
21  
22  
23  
24  
25

### 26 **References**

- 27  
28 Ancey C., Davison A. C., Bohm T., Jodeau M. & Frey P. (2008) Entrainment and motion of  
29 coarse particles in a shallow water stream down a steep slope. *Journal of Fluid Mechanics*,  
30 **595**, 83-114.  
31  
32 Andrews E. D. (1984) Bed-material entrainment and hydraulic geometry of gravel-bed rivers  
33 in Colorado. *Geological Society of America Bulletin*, **95**, 371-378.  
34  
35 Andrews E. D. (1983) Entrainment of gravel from naturally sorted riverbed material.  
36 *Geological Society of America Bulletin*, **94**, 1225-1231.  
37  
38 Ashworth P. J. & Ferguson R. I. (1989) Size-selective entrainment of bed-load in gravel bed  
39 streams. *Water Resources Research*, **25**, 627-634.  
40  
41 Baker V. R. & Ritter D. F. (1975) Competence of rivers to transport coarse bedload material.  
42 *Geological Society of America Bulletin*, **86**, 975-978.  
43  
44 Barquin J. & Death R. G. (2006) Spatial patterns of macroinvertebrate diversity in New  
45 Zealand springbrooks and rhithral streams. *Journal of the North American Benthological*  
46 *Society*, **25**, 768-786.  
47  
48 Barry J. J. (2004) A general power equation for predicting bed load transport rates in gravel  
49 bed rivers. *Water Resources Research*, **40**, W10401.  
50  
51 Bartnik W., Madeyski M. & Michalik A. (1992) Suspended load and bed load transport in  
52 mountain streams determined by different methods. In *Erosion and sediment transport*  
53 *monitoring programs in river basins*, vol. 210 (ed. D. E. Walling, J. Bogen & T. J. Day), pp.  
54 3-9. Wallingford, Oxfordshire: International Association of Hydrological Sciences.  
55  
56 Batalla R. J. (1997) Evaluating bed-material transport equations using field measurements in  
57 a sandy gravel-bed stream, Arbucies River, NE Spain. *Earth Surface Processes and*  
58 *Landforms*, **22**, 121-130.  
59  
60



- 1  
2  
3 Bathurst J. C., Graf W. H. & Cao H. H. (1987) Bed load discharge equations for steep  
4 mountain rivers. In *Sediment transport in gravel-bed rivers* (ed. C. R. Thorne, J. C. Bathurst  
5 & R. D. Hey), pp. 453-491. New York: John Wiley.
- 6  
7 Bhowmik N. G. (1982) Shear stress distribution and secondary currents in straight open  
8 channels. In *Gravel-bed rivers* (ed. R. D. Hey, J. C. Bathurst & C. R. Thorne), pp. 31-61.  
9 Chichester: John Wiley & Sons.
- 10  
11 Biggs B. J. E. (1996) Patterns in benthic algae of streams. In *Algal ecology: Freshwater*  
12 *benthic ecosystems* (ed. R. J. Stevenson, M. L. Bothwell & R. L. Lowe), pp. 31-56. San  
13 Diego: Academic Press.
- 14  
15 Biggs B. J. F., Duncan M. J., Suren A. M. & Holomuzki J. R. (2001) The importance of bed  
16 sediment stability to benthic ecosystems of streams. In *Gravel bed rivers V* (ed. M. P.  
17 Mosley), pp. 423-449. Wellington: New Zealand Hydrological Society.
- 18  
19 Biggs B. J. F., Smith R. A. & Duncan M. J. (1999) Velocity and sediment disturbance of  
20 periphyton in headwater streams: Biomass and metabolism. *Journal of the North American*  
21 *Benthological Society*, **18**, 222-241.
- 22  
23 Bogen J. & Moen K. (2003) Bed load measurements with a new passive acoustic sensor. In  
24 *Erosion and sediment transport measurement in rivers: Technological and methodological*  
25 *advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 181-192. Wallingford,  
26 Oxfordshire: International Association of Hydrological Sciences.
- 27  
28 Bond N. R. (2004) Spatial variation in fine sediment transport in small upland streams: The  
29 effects of flow regulation and catchment geology. *River Research and Applications*, **20**, 705-  
30 717.
- 31  
32 Bond N. R. & Downes B. J. (2000) Flow-related disturbance in streams: An experimental test  
33 of the role of rock movement in reducing macroinvertebrate population densities. *Marine and*  
34 *Freshwater Research*, **51**, 333-337.
- 35  
36 Bond N. R. & Downes B. J. (2003) The independent and interactive effects of fine sediment  
37 and flow on benthic invertebrate communities characteristic of small upland streams.  
38 *Freshwater Biology*, **48**, 455-465.
- 39  
40 Brasington J., Langham J. & Rumsby B. (2003) Methodological sensitivity of morphometric  
41 estimates of coarse fluvial sediment transport. *Geomorphology*, **53**, 299-316.
- 42  
43 Brasington J., Rumsby B. T. & McVey R. A. (2000) Monitoring and modelling  
44 morphological change in a braided gravel-bed river using high resolution GPS-based survey.  
45 *Earth Surface Processes and Landforms*, **25**, 973-990.
- 46  
47 Bray D. I. (1980) Evaluation of effective boundary roughness for gravel-bed rivers. *Canadian*  
48 *Journal of Civil Engineering*, **7**, 392-397.
- 49  
50 Brewer P. A., Leeks G. J. L. & Lewin J. (1992) Direct measurement of in-channel abrasion  
51 processes. In *Erosion and sediment transport monitoring programs in river basins*, vol. 210  
52 (ed. D. E. Walling, J. Bogen & T. J. Day), pp. 21-29. Wallingford, Oxfordshire: International  
53 Association of Hydrological Sciences.
- 54  
55 Brewer P. A. & Passmore D. G. (2002) Sediment budgeting techniques in gravel-bed rivers.  
56 In *Sediment flux to basins: Causes, controls and consequences*, vol. 191 (ed. S. J. Jones & L.  
57 E. Frostick), pp. 97-113. London: Geological Society.
- 58  
59 Buffington J. M. & Montgomery D. R. (1997) A systematic analysis of eight decades of  
60 incipient motion studies, with special reference to gravel-bedded rivers. *Water Resources*  
*Research*, **33**, 1993-2029.

- 1  
2  
3 Bunte K. (1996) Analyses of the temporal variation of coarse bedload transport and its grain  
4 size distribution: Squaw Creek, Montana, USA. *General Technical Report - Rocky Mountain*  
5 *Forest and Range Experiment Station, USDA Forest Service*, 123 pp.
- 6  
7 Bunte K. & Abt S. R. (2003) Sampler size and sampling time affect bed load transport rates  
8 and particle sizes measured with bed load traps in gravel bed streams. In *Erosion and*  
9 *sediment transport measurement in rivers: Technological and methodological advances*, vol.  
10 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 126-133. Wallingford, Oxfordshire:  
11 International Association of Hydrological Sciences.
- 12  
13 Bunte K., Abt S. R., Potyondy J. P. & Ryan S. E. (2004) Measurement of coarse gravel and  
14 cobble transport using portable bedload traps. *Journal of Hydraulic Engineering-Asce*, **130**,  
15 879-893.
- 16  
17 Busskamp R. & Hasholt B. (1996) Coarse bed load transport in a glacial valley, Sermilik,  
18 South East Greenland. *Zeitschrift für Geomorphologie*, **40**, 349-358.
- 19  
20 Campbell A. J. & Sidle R. C. (1985) Bedload transport in a pool-riffle sequence of a coastal  
21 Alaska stream. *Water Resources Bulletin*, **21**, 579-590.
- 22  
23 Carling P. A., Williams J. J., Kelsey A., Glaister M. S. & Orr H. G. (1998) Coarse bedload  
24 transport in a mountain river. *Earth Surface Processes and Landforms*, **23**, 141-157.
- 25  
26 Carson M. A. & Griffiths G. A. (1987) Bedload transport in gravel channels. *Journal of*  
27 *Hydrology (New Zealand)*, **26**, 1-151.
- 28  
29 Chappell A., Heritage G. L., Fuller I. C., Large A. R. G. & Milan D. J. (2003) Geostatistical  
30 analysis of ground-survey elevation data to elucidate spatial and temporal river channel  
31 change. *Earth Surface Processes and Landforms*, **28**, 349-370.
- 32  
33 Cobb D. G., Galloway T. D. & Flannagan J. F. (1992) Effects of discharge and substrate  
34 stability on density and species composition of stream insects. *Canadian Journal of Fisheries*  
35 *and Aquatic Sciences*, **49**, 1788-1795.
- 36  
37 Culp J. M., Wrona F. J. & Davies R. W. (1986) Response of stream benthos and drift to fine  
38 sediment deposition versus transport. *Canadian Journal of Zoology-Revue Canadienne De*  
39 *Zoologie*, **64**, 1345-1351.
- 40  
41 Death R. G. (2008) Effects of floods on aquatic invertebrate communities. In *Aquatic insects:*  
42 *Challenges to populations* (ed. J. Lancaster & R. A. Briers), pp. 103-121: CAB International.
- 43  
44 Death R. G. (2002) Predicting invertebrate diversity from disturbance regimes in forest  
45 streams. *Oikos*, **97**, 18-30.
- 46  
47 Death R. G. & Winterbourn M. J. (1994) Environmental stability and community persistence  
48 - a multivariate perspective. *Journal of the North American Benthological Society*, **13**, 125-  
49 139.
- 50  
51 Death R. G. & Winterbourn M. J. (1995) Diversity patterns in stream benthic invertebrate  
52 communities: The influence of habitat stability. *Ecology*, **76**, 1446-1460.
- 53  
54 Death R. G. & Zimmermann E. M. (2005) Interaction between disturbance and primary  
55 productivity in determining stream invertebrate diversity. *Oikos*, **111**, 392-402.
- 56  
57 Dietrich W. E., Kirchner J. W., Ikeda H. & Iseya F. (1989) Sediment supply and the  
58 development of the coarse surface-layer in gravel-bedded rivers. *Nature*, **340**, 215-217.
- 59  
60 Dittrich A. & Schmedtje U. (1995) Indicating shear-stress with FST-hemispheres - effects of  
stream-bottom topography and water depth. *Freshwater Biology*, **34**, 107-121.

- 1  
2  
3 Doledec S., Lamouroux N., Fuchs U. & Merigoux S. (2007) Modelling the hydraulic  
4 preferences of benthic macroinvertebrates in small European streams. *Freshwater Biology*, **52**,  
5 145-164.
- 6  
7 Dollar E. S. J. (2002) Fluvial geomorphology. *Progress in Physical Geography*, **26**, 123-143.
- 8  
9 Downes B. J., Glaister A. & Lake P. S. (1997) Spatial variation in the force required to  
10 initiate rock movement in 4 upland streams: Implications for estimating disturbance  
11 frequencies. *Journal of the North American Benthological Society*, **16**, 203-220.
- 12  
13 Downes B. J., Lake P. S., Glaister A. & Webb J. A. (1998) Scales and frequencies of  
14 disturbances: Rock size, bed packing and variation among upland streams. *Freshwater  
15 Biology*, **40**, 625-639.
- 16  
17 Downing J., Farley P. J., Bunte K., Swingle K., Ryan S. E. & Dixon M. (2003) Acoustic  
18 gravel-transport sensor: Description and field tests in Little Granite Creek, Wyoming, USA.  
19 In *Erosion and sediment transport measurement in rivers: Technological and methodological  
20 advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 193-200. Wallingford,  
21 Oxfordshire: International Association of Hydrological Sciences.
- 22  
23 Duan J. G. & Scott S. (2007) Selective bed-load transport in Las Vegas wash, a gravel-bed  
24 stream. *Journal of Hydrology*, **342**, 320-330.
- 25  
26 Duncan M. J., Suren A. M. & Brown S. L. R. (1999) Assessment of streambed stability in  
27 steep, bouldery streams: Development of a new analytical technique. *Journal of the North  
28 American Benthological Society*, **18**, 445-456.
- 29  
30 Effenberger M., Sailer G., Townsend C. R. & Matthaei C. D. (2006) Local disturbance  
31 history and habitat parameters influence the microdistribution of stream invertebrates.  
32 *Freshwater Biology*, **51**, 312-332.
- 33  
34 Ergenzinger P. (1985) Electromagnetic devices for measuring bedload transport.  
35 *Sedimentology*, **32**, 159-159.
- 36  
37 Ergenzinger P. & Conrady J. (1982) A new tracer technique for measuring bedload in natural  
38 channels. *Catena*, **9**, 77-80.
- 39  
40 Ergenzinger P. & de Jong C. (2003) Perspectives on bed load measurement. In *Erosion and  
41 sediment transport measurement in rivers: Technological and methodological advances*, vol.  
42 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 113-125. Wallingford, Oxfordshire:  
43 International Association of Hydrological Sciences.
- 44  
45 Ergenzinger P., Schmidt K. H. & Busskamp R. (1989) The pebble transmitter system (PETS)  
46 - 1st results of a technique for studying coarse material erosion, transport and deposition.  
47 *Zeitschrift für Geomorphologie*, **33**, 503-508.
- 48  
49 Ferguson R. I. (1994) Critical discharge for entrainment of poorly sorted gravel. *Earth  
50 Surface Processes and Landforms*, **19**, 179-186.
- 51  
52 Ferguson R. I. (2003) The missing dimension: Effects of lateral variation on 1-D calculations  
53 of fluvial bedload transport. *Geomorphology*, **56**, 1-14.
- 54  
55 Ferguson R. I. & Ashworth P. J. (1992) Spatial patterns of bedload transport and channel  
56 change in braided and near braided rivers. In *Dynamics of gravel-bed rivers* (ed. P. Billi, R. D.  
57 Hey, C. R. Thorne & P. Tacconi), pp. 477-492. Chichester: Wiley.
- 58  
59 Ferguson R. I., Bloomer D. J., Hoey T. B. & Werritty A. (2002) Mobility of river tracer  
60 pebbles over different timescales. *Water Resources Research*, **38**, 1045.

1  
2  
3 Ferguson R. I. & Hoey T. B. (2002) Long-term slowdown of river tracer pebbles: Generic  
4 models and implications for interpreting short-term tracer studies. *Water Resources Research*,  
5 **38**, 1142.

6  
7 Ferguson R. I. & Wathen S. J. (1998) Tracer-pebble movement along a concave river profile:  
8 Virtual velocity in relation to grain size and shear stress. *Water Resources Research*, **34**,  
9 2031-2038.

10  
11 Froehlich W. (2003) Monitoring bed load transport using acoustic and magnetic devices. In  
12 *Erosion and sediment transport measurement in rivers: Technological and methodological*  
13 *advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 201-210. Wallingford,  
14 Oxfordshire: International Association of Hydrological Sciences.

15  
16 Frutiger A. & Schib J. L. (1993) Limitations of FST hemispheres in lotic benthos research.  
17 *Freshwater Biology*, **30**, 463-474.

18  
19 Fryirs K. A., Brierley G. J., Preston N. J. & Kasai M. (2007) Buffers, barriers and blankets:  
20 The (dis)connectivity of catchment-scale sediment cascades. *Catena*, **70**, 49-67.

21  
22 Fuller I. C. & Hutchinson E. L. (2007) Sediment flux in a small gravel-bed stream: Response  
23 to channel remediation works. *New Zealand Geographer*, **63**, 169-180.

24  
25 Fuller I. C., Large A. R. G., Charlton M. E., Heritage G. L. & Milan D. J. (2003a) Reach-  
26 scale sediment transfers: An evaluation of two morphological budgeting approaches. *Earth*  
27 *Surface Processes and Landforms*, **28**, 889-903.

28  
29 Fuller I. C., Large A. R. G., Heritage G. L., Milan D. J. & Charlton M. E. (2005) Derivation  
30 of annual reach-scale sediment transfer in the River Coquet, Northumberland, UK. In *Fluvial*  
31 *geomorphology VII*, vol. 35 (ed. M. D. Blum, S. B. Mariott & S. F. Leclair), pp. 61-74.  
32 Oxford: Blackwell.

33  
34 Fuller I. C., Large A. R. G. & Milan D. J. (2003b) Quantifying channel development and  
35 sediment transfer following chute cutoff in a wandering gravel-bed river. *Geomorphology*, **54**,  
36 307-323.

37  
38 Fuller I. C., Passmore D. G., Heritage G. L., Large A. R. G., Milan D. J. & Brewer P. A.  
39 (2002) Annual sediment budgets in an unstable gravel-bed river: The River Coquet, Northern  
40 England. In *Sediment flux to basins: Causes, controls and consequences*, vol. 191 (ed. S. J.  
41 Jones & L. E. Frostick), pp. 115-131. London: Geological Society.

42  
43 Giberson D. J. & Caissie D. (1998) Stream habitat hydraulics: Interannual variability in three  
44 reaches of Catamaran Brook, New Brunswick. *Canadian Journal of Fisheries and Aquatic*  
45 *Sciences*, **55**, 485-494.

46  
47 Gomez B. (1991) Bedload transport. *Earth-Science Reviews*, **31**, 89-132.

48  
49 Gomez B. & Church M. (1989) An assessment of bed load sediment transport formulae for  
50 gravel bed rivers. *Water Resources Research*, **25**, 1161-1186.

51  
52 Gordon N. D., McMahon T. A. & Finlayson B. L. (1992) *Stream hydrology: An introduction*  
53 *for ecologists*. New York: John Wiley and Sons.

54  
55 Gore J. A. (1996) Discharge measurements and streamflow analysis. In *Methods in stream*  
56 *ecology* (ed. F. R. Hauer & G. A. Lamberti), pp. 53-74. San Diego: Academic Press.

57  
58 Gore J. A., Niemela S., Resh V. H. & Statzner B. (1994) Near-substrate hydraulic conditions  
59 under artificial floods from peaking hydropower operation - a preliminary-analysis of  
60 disturbance intensity and duration. *Regulated Rivers-Research & Management*, **9**, 15-34.



- 1  
2  
3 Gottesfeld A. S. & Tunncliffe J. (2003) Bed load measurements with a passive magnetic  
4 induction device. In *Erosion and sediment transport measurement in rivers: Technological  
5 and methodological advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 211-  
6 221. Wallingford, Oxfordshire: International Association of Hydrological Sciences.  
7
- 8 Habersack H. M. (2001) Radio-tracking gravel particles in a large braided river in New  
9 Zealand: A field test of the stochastic theory of bed load transport proposed by Einstein.  
10 *Hydrological Processes*, **15**, 377-391.  
11
- 12 Habersack H. M. (2003) Use of radio-tracking techniques in bed load transport investigations.  
13 In *Erosion and sediment transport measurement in rivers: Technological and methodological  
14 advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 172-180. Wallingford,  
15 Oxfordshire: International Association of Hydrological Sciences.  
16
- 17 Habersack H. M. & Laronne J. B. (2002) Evaluation and improvement of bed load discharge  
18 formulas based on Helley-Smith sampling in an alpine gravel bed river. *Journal of Hydraulic  
19 Engineering-Asce*, **128**, 484-499.  
20
- 21 Hallisey J. E. & Belt G. H. (1996) Relationships between particle movement and channel  
22 morphology in some northern Idaho streams. *Water Resources Bulletin*, **32**, 383-391.  
23
- 24 Hardardottir J. & Snorrason A. (2003) Sediment monitoring of glacial rivers in Iceland: New  
25 data on bed load transport. In *Erosion and sediment transport measurement in rivers:  
26 Technological and methodological advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E.  
27 Walling), pp. 154-163. Wallingford, Oxfordshire: International Association of Hydrological  
28 Sciences.  
29
- 30 Hardison B. S. & Layzer J. B. (2001) Relations between complex hydraulics and the  
31 localized distribution of mussels in three regulated rivers. *Regulated Rivers-Research &  
32 Management*, **17**, 77-84.  
33
- 34 Hassan M. A. & Church M. (2001) Sensitivity of bed load transport in Harris Creek: Seasonal  
35 and spatial variation over a cobble-gravel bar. *Water Resources Research*, **37**, 813-825.  
36
- 37 Hassan M. A., Church M. & Ashworth P. J. (1992) Virtual rate and mean distance of travel of  
38 individual clasts in gravel-bed channels. *Earth Surface Processes and Landforms*, **17**, 617-  
39 627.  
40
- 41 Hassan M. A., Church M. & Schick A. P. (1991) Distance of movement of coarse particles in  
42 gravel bed streams. *Water Resources Research*, **27**, 503-511.  
43
- 44 Heritage G. L. & Milan D. J. (2004) A conceptual model of the role of excess energy in the  
45 maintenance of a riffle-pool sequence. *Catena*, **58**, 235-257.  
46
- 47 Hey R. D. (1979) Flow resistance in gravel-bed rivers. *Journal of the Hydraulics Division-  
48 Asce*, **105**, 365-379.  
49
- 50 Hoey T., Cudden J. & Shvidchenko A. (2001) The consequences of unsteady sediment  
51 transport in braided rivers. In *Gravel bed rivers V* (ed. M. P. Mosley), pp. 121-142.  
52 Wellington: New Zealand Hydrological Society.  
53
- 54 Holomuzki J. R. & Biggs B. J. F. (2000) Taxon-specific responses to high-flow disturbance  
55 in streams: Implications for population persistence. *Journal of the North American  
56 Benthological Society*, **19**, 670-679.  
57
- 58 Hooke J. (2003) Coarse sediment connectivity in river channel systems: A conceptual  
59 framework and methodology. *Geomorphology*, **56**, 79-94.  
60
- 61 Knighton D. (2008) *Fluvial forms and processes: A new perspective*. London: Arnold.

1  
2  
3 Komar P. D. (1989) Flow-competence evaluations of the hydraulic parameters of floods: An  
4 assessment of the technique. In *Floods: Hydrological, sedimentological and*  
5 *geomorphological implications*. (ed. K. Beven & P. A. Carling), pp. 107-133. New York:  
6 John Wiley and Sons.

7  
8 Komar P. D. (1987) Selective grain entrainment by a current from a bed of mixed sizes - a  
9 reanalysis. *Journal of Sedimentary Petrology*, **57**, 203-211.

10  
11 Kondolf G. M. & Matthews W. V. G. (1986) Transport of tracer gravels on a coastal  
12 California river. *Journal of Hydrology*, **85**, 265-280.

13  
14 Kostaschuk R., Best J., Villard P., Peakall J. & Franklin M. (2005) Measuring flow velocity  
15 and sediment transport with an acoustic doppler current profiler. *Geomorphology*, **68**, 25-37.

16  
17 Kurashige Y. (2002) Topographical changes and sediment transport after habitat  
18 improvement in the Pakenai River, Japan. In *The structure, function and management*  
19 *implications of fluvial sedimentary systems*, vol. 276 (ed. F. J. Dyer, M. C. Thoms & J. M.  
20 Olley), pp. 93-102. Wallingford, Oxfordshire: International Association of Hydrological  
21 Sciences.

22  
23 Lake P. S. (2000) Disturbance, patchiness, and diversity in streams. *Journal of the North*  
24 *American Benthological Society*, **19**, 573-592.

25  
26 Lamouroux N., Statzner B., Fuchs U., Kohmann F. & Schmedtje U. (1992) An  
27 unconventional approach to modeling spatial and temporal variability of local shear-stress in  
28 stream segments. *Water Resources Research*, **28**, 3251-3258.

29  
30 Lancaster J. & Hildrew A. G. (1993a) Flow refugia and the microdistribution of lotic  
31 macroinvertebrates. *Journal of the North American Benthological Society*, **12**, 385-393.

32  
33 Lancaster J. & Hildrew A. G. (1993b) Characterizing in-stream flow refugia. *Canadian*  
34 *Journal of Fisheries and Aquatic Sciences*, **50**, 1663-1675.

35  
36 Lane E. W. (1955) Design of stable channels. *Transactions of the American Society of Civil*  
37 *Engineers*, **120**, 1234-1260.

38  
39 Lane S. N. (2001) The measurement of gravel-bed river morphology. In *Gravel bed rivers V*  
40 (ed. M. P. Mosley), pp. 291-337. Wellington: New Zealand Hydrological Society.

41  
42 Lane S. N., Chandler J. H. & Richards K. S. (1994) Developments in monitoring and  
43 modelling small-scale river bed topography *Earth Surface Processes and Landforms*, **19**,  
44 349-368.

45  
46 Lane S. N., Westaway R. M. & Hicks D. M. (2003) Estimation of erosion and deposition  
47 volumes in a large, gravel-bed, braided river using synoptic remote sensing. *Earth Surface*  
48 *Processes and Landforms*, **28**, 249-271.

49  
50 Laronne J. B., Alexandrov Y., Bergman N., Cohen H., Garcia C., Habersack H. M., Powell D.  
51 M. & Reid I. (2003) The continuous monitoring of bed load flux in various fluvial  
52 environments. In *Erosion and sediment transport measurement in rivers: Technological and*  
53 *methodological advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E. Walling), pp. 134-145.  
54 Wallingford, Oxfordshire: International Association of Hydrological Sciences.

55  
56 Laronne J. B. & Duncan M. J. (1992) Bedload transport paths and gravel bar formation. In  
57 *Dynamics of gravel-bed rivers* (ed. P. Billi, R. D. Hey, C. R. Thorne & P. Tacconi).  
58 Chichester: John Wiley & sons.

59  
60 Laronne J. B., Garcia C. & Reid I. (2001) Mobility of patch sediment in gravel bed streams:  
Patch character and its implications for bedload. In *Gravel bed rivers V* (ed. M. P. Mosley),  
pp. 249-289. Wellington: New Zealand Hydrological Society.

- 1  
2  
3 Laronne J. B., Outhet D. N., Carling P. A. & McCabe T. J. (1994) Scour chain employment  
4 in gravel-bed rivers. *Catena*, **22**, 299-306.
- 5  
6 Laronne J. B., Outhet D. N., Duckham J. L. & McCabe T. J. (1992) Determining event  
7 bedload volumes for evaluation of potential degradation sites due to gravel extraction,  
8 N.S.W., Australia. In *Erosion and sediment transport monitoring programs in river basins*,  
9 vol. 210 (ed. D. E. Walling, J. Bogen & T. J. Day), pp. 87-94. Wallingford, Oxfordshire:  
10 International Association of Hydrological Sciences.
- 11  
12 Leopold L. B. (1992) Sediment size that determines channel morphology. In *Dynamics of*  
13 *gravel bed rivers* (ed. P. Billi, R. D. Hey, C. R. Thorne & P. Tacconi), pp. 297-311.  
14 Chichester: Wiley.
- 15  
16 Lewin J. & Brewer P. A. (2002) Laboratory simulation of clast abrasion. *Earth Surface*  
17 *Processes and Landforms*, **27**, 145-164.
- 18  
19 Lewis J. (1991) An improved bedload sampler. In *Fifth Federal Interagency Sedimentation*  
20 *Conference Proceedings* (ed. S. Fan & Y. H. Kuo), pp. 6-1 - 6-8. Las Vegas: Pacific  
21 Southwest Research Station.
- 22  
23 Lisle T. E., Nelson J. M., Pitlick J., Madej M. A. & Barkett B. L. (2000) Variability of bed  
24 mobility in natural, gravel-bed channels and adjustments to sediment load at local and reach  
25 scales. *Water Resources Research*, **36**, 3743-3755.
- 26  
27 Lorang M. S. & Hauer F. R. (2003) Flow competence and streambed stability: An evaluation  
28 of technique and application. *Journal of the North American Benthological Society*, **22**, 475-  
29 491.
- 30  
31 Martin-Vide J. P., Ninerola D., Bateman A., Navarro A. & Velasco E. (1999) Runoff and  
32 sediment transport in a torrential ephemeral stream of the mediterranean coast. *Journal of*  
33 *Hydrology*, **225**, 118-129.
- 34  
35 Martin Y. & Church M. (1995) Bed-material transport estimated from channel surveys -  
36 Vedder River, British-Columbia. *Earth Surface Processes and Landforms*, **20**, 347-361.
- 37  
38 Martin Y. & Church M. (2000) Re-examination of Bagnold's empirical bedload formulae.  
39 *Earth Surface Processes and Landforms*, **25**, 1011-1024.
- 40  
41 Martin Y. & Ham D. (2005) Testing bedload transport formulae using morphologic transport  
42 estimates and field data: Lower Fraser River, British Columbia. *Earth Surface Processes and*  
43 *Landforms*, **30**, 1265-1282.
- 44  
45 Matthaei C. D., Arbuckle C. J. & Townsend C. R. (2000) Stable surface stones as refugia for  
46 invertebrates during disturbance in a New Zealand stream. *Journal of the North American*  
47 *Benthological Society*, **19**, 82-93.
- 48  
49 Matthaei C. D., Guggelberger C. & Huber H. (2003) Local disturbance history affects  
50 patchiness of benthic river algae. *Freshwater Biology*, **48**, 1514-1526.
- 51  
52 Matthaei C. D., Peacock K. A. & Townsend C. R. (1999a) Patchy surface stone movement  
53 during disturbance in a New Zealand stream and its potential significance for the fauna.  
54 *Limnology and Oceanography*, **44**, 1091-1102.
- 55  
56 Matthaei C. D., Peacock K. A. & Townsend C. R. (1999b) Scour and fill patterns in a New  
57 Zealand stream and potential implications for invertebrate refugia. *Freshwater Biology*, **42**,  
58 41-57.
- 59  
60 Matthaei C. D., Uehlinger U., Meyer E. I. & Frutiger A. (1996) Recolonization by benthic  
invertebrates after experimental disturbance in a Swiss prealpine river. *Freshwater Biology*,  
**35**, 233-248.



- 1  
2  
3 McEwan I. K., Habersack H. M. & Heald J. G. C. (2001) Discrete particle modelling and  
4 active tracers: New techniques for studying sediment transport as a lagrangian phenomenon.  
5 In *Gravel bed rivers V* (ed. M. P. Mosley), pp. 339-367. Wellington: New Zealand  
6 Hydrological Society.
- 7  
8 McIntosh A. R. (2000) Habitat- and size-related variations in exotic trout impacts on native  
9 galaxiid fishes in New Zealand streams. *Canadian Journal of Fisheries and Aquatic Sciences*,  
10 **57**, 2140-2151.
- 11  
12 Merigoux S. & Doledec S. (2004) Hydraulic requirements of stream communities: A case  
13 study on invertebrates. *Freshwater Biology*, **49**, 600-613.
- 14  
15 Milan D. J., Heritage G. L., Large A. R. G. & Charlton M. E. (2001) Stage dependent  
16 variability in tractive force distribution through a riffle-pool sequence. *Catena*, **44**, 85-109.
- 17  
18 Miller M. C., McCave I. N. & Komar P. D. (1977) Threshold of sediment motion under  
19 unidirectional currents. *Sedimentology*, **24**, 507-527.
- 20  
21 Mizuyama T., Fujita M. & Nonaka M. (2003) Measurement of bed load with the use of  
22 hydrophones in mountain torrents. In *Erosion and sediment transport measurement in rivers:  
23 Technological and methodological advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E.  
24 Walling), pp. 222-227. Wallingford, Oxfordshire: International Association of Hydrological  
25 Sciences.
- 26  
27 Mosley M. P. (1978) Bed material transport in the Tamaki River near Dannevirke, North  
28 Island, New Zealand *New Zealand Journal of Science*, **21**, 619-626.
- 29  
30 Muotka T. & Virtanen R. (1995) The stream as a habitat templet for bryophytes - species  
31 distributions along gradients in disturbance and substratum heterogeneity. *Freshwater  
32 Biology*, **33**, 141-160.
- 33  
34 Newbury R. W. (1984) Hydrologic determinants of aquatic insect habitats. In *The ecology of  
35 aquatic insects*. (ed. V. H. Resh & D. M. Rosenberg), pp. 323-357. New York: Praeger  
36 Publishers.
- 37  
38 Palmer M. A., Bely A. E. & Berg K. E. (1992) Response of invertebrates to lotic disturbance  
39 - a test of the hyporheic refuge hypothesis. *Oecologia*, **89**, 182-194.
- 40  
41 Parker G. (1990) Surface-based bedload transport relation for gravel rivers *Journal of  
42 Hydraulic Research*, **28**, 417-436.
- 43  
44 Parker G., Klingeman P. C. & McLean D. G. (1982) Bedload and size distribution in paved  
45 gravel-bed streams. *Journal of the Hydraulics Division-Asce*, **108**, 544-571.
- 46  
47 Peterson C. G. (1996) Response of benthic algal communities to natural physical disturbance.  
48 In *Algal ecology: Freshwater benthic ecosystems* (ed. R. J. Stevenson, M. L. Bothwell & R. L.  
49 Lowe), pp. 375-402. San Diego: Academic Press.
- 50  
51 Pfankuch D. J. (1975) Stream reach inventory and channel stability evaluation.: U.S.D.A.  
52 Forest Service, Region 1, Missoula, Montana.
- 53  
54 Poff N. L. (1992) Why disturbances can be predictable - a perspective on the definition of  
55 disturbance in streams. *Journal of the North American Benthological Society*, **11**, 86-92.
- 56  
57 Powell D. M. (1998) Patterns and processes of sediment sorting in gravel-bed rivers.  
58 *Progress in Physical Geography*, **22**, 1-32.
- 59  
60 Powell D. M. & Ashworth P. J. (1995) Spatial pattern of flow competence and bed-load  
transport in a divided gravel-bed river. *Water Resources Research*, **31**, 741-752.

- 1  
2  
3 Reice S. R., Wissmar R. C. & Naiman R. J. (1990) Disturbance regimes, resilience, and  
4 recovery of animal communities and habitats in lotic ecosystems. *Environmental*  
5 *Management*, **14**, 647-659.
- 6  
7 Rennie C. D. & Millar R. G. (2004) Measurement of the spatial distribution of fluvial  
8 bedload transport velocity in both sand and gravel. *Earth Surface Processes and Landforms*,  
9 **29**, 1173-1193.
- 10  
11 Resh V. H., Brown A. V., Covich A. P., Gurtz M. E., Li H. W., Minshall G. W., Reice S. R.,  
12 Sheldon A. L., Wallace J. B. & Wissmar R. C. (1988) The role of disturbance in stream  
13 ecology. *Journal of the North American Benthological Society*, **7**, 433-455.
- 14  
15 Richardson K., Benson I. & Carling P. A. (2003) An instrument to record sediment  
16 movement in bedrock channels. In *Erosion and sediment transport measurement in rivers:*  
17 *Technological and methodological advances*, vol. 283 (ed. J. Bogen, T. Fergus & D. E.  
18 Walling), pp. 228-235. Wallingford, Oxfordshire: International Association of Hydrological  
19 Sciences.
- 20  
21 Rickenmann D. & McArdeall B. W. (2007) Continuous measurement of sediment transport in  
22 the Erlenbach stream using piezoelectric bedload impact sensors. *Earth Surface Processes*  
23 *and Landforms*, **32**, 1362-1378.
- 24  
25 Robert A. (1990) Boundary roughness in coarse-grained channels. *Progress in Physical*  
26 *Geography*, **14**, 42-70.
- 27  
28 Rosenberg D. M. & Wiens A. P. (1978) Effects of sediment addition on macrobenthic  
29 invertebrates in a northern Canadian river. *Water Research*, **12**, 753-763.
- 30  
31 Salehi F., Lagace R. & Pesant A. R. (1997) Construction of a year-round operating gauging  
32 station for sediment and water quality measurements of small watersheds. *Journal of Soil and*  
33 *Water Conservation*, **52**, 431-436.
- 34  
35 Scarsbrook M. R. & Townsend C. R. (1993) Stream community structure in relation to spatial  
36 and temporal variation - a habitat templet study of 2 contrasting New-Zealand streams.  
37 *Freshwater Biology*, **29**, 395-410.
- 38  
39 Schmidt K. H. & Ergenzinger P. (1992) Bedload entrainment, travel lengths, step lengths,  
40 rest periods - studied with passive (iron, magnetic) and active (radio) tracer techniques. *Earth*  
41 *Surface Processes and Landforms*, **17**, 147-165.
- 42  
43 Schmidt K. H. & Gintz D. (1995) Results of bedload tracer experiments in a mountain river.  
44 In *River geomorphology* (ed. E. Hickin), pp. 145-158. Chichester: John Wiley & Sons.
- 45  
46 Sear D. A. (2003) Event bed load yield measurement with load cell bed load traps and  
47 prediction of bed load yield from hydrograph shape. In *Erosion and sediment transport*  
48 *measurement in rivers: Technological and methodological advances*, vol. 283 (ed. J. Bogen,  
49 T. Fergus & D. E. Walling), pp. 146-153. Wallingford, Oxfordshire: International  
50 Association of Hydrological Sciences.
- 51  
52 Sear D. A. (1996) Sediment transport processes in pool-riffle sequences. *Earth Surface*  
53 *Processes and Landforms*, **21**, 241-262.
- 54  
55 Sear D. A., Damon W., Booker D. J. & Anderson D. G. (2000a) A load cell based continuous  
56 recording bedload trap. *Earth Surface Processes and Landforms*, **25**, 659-672.
- 57  
58 Sear D. A., Lee M. W. E., Carling P. A., Oakey R. J. & Collins M. B. (2003) An assessment  
59 of the accuracy of the spatial integration method (SIM) for estimating coarse bedload  
60 transport in gravel-bedded streams using tracers. In *Erosion and sediment transport*  
*measurement in rivers: Technological and methodological advances*, vol. 283 (ed. J. Bogen,

- 1  
2  
3 T. Fergus & D. E. Walling), pp. 164-171. Wallingford, Oxfordshire: International  
4 Association of Hydrological Sciences.
- 5  
6 Sear D. A., Lee M. W. E., Oakey R. J., Carling P. A. & Collins M. B. (2000b) Coarse  
7 sediment tracing technology in littoral and fluvial environments: A review. In *Tracers in*  
8 *geomorphology* (ed. I. D. L. Foster), pp. 21-55. Chichester: Wiley & Sons.
- 9  
10 Shields A. (1936) Anwendung der Ähnlichkeitsmechanik und der Turbulenzforschung auf  
11 die Geschiebebewegung. *Mitteilungen der Preussischen Versuchsanstalt für Wasserbau und*  
12 *Schiffbau*, **26**.
- 13  
14 Shvidchenko A. B., Pender G. & Hoey T. B. (2001) Critical shear stress for incipient motion  
15 of sand/gravel streambeds. *Water Resources Research*, **37**, 2273-2283.
- 16  
17 Sklar L. S. & Dietrich W. E. (2004) A mechanistic model for river incision into bedrock by  
18 saltating bed load. *Water Resources Research*, **40**, W06301.
- 19  
20 Statzner B. (1993) Limitations of FST hemispheres in lotic benthos research - response.  
21 *Freshwater Biology*, **30**, 475-483.
- 22  
23 Statzner B., Gore J. A. & Resh V. H. (1988) Hydraulic stream ecology - observed patterns  
24 and potential applications. *Journal of the North American Benthological Society*, **7**, 307-360.
- 25  
26 Statzner B., Kohmann F. & Hildrew A. G. (1991) Calibration of FST-hemispheres against  
27 bottom shear-stress in a laboratory flume. *Freshwater Biology*, **26**, 227-231.
- 28  
29 Statzner B. & Muller R. (1989) Standard hemispheres as indicators of flow characteristics in  
30 lotic benthos research. *Freshwater Biology*, **21**, 445-459.
- 31  
32 Stott T. & Sawyer A. (2000) Clast travel distances and abrasion rates in two coarse upland  
33 channels determined using magnetically tagged bedload. In *Tracers in geomorphology* (ed. I.  
34 D. L. Foster), pp. 389-399. Chichester: Wiley & Sons.
- 35  
36 Suren A. M. (1996) Bryophyte distribution patterns in relation to macro-, meso-, and micro-  
37 scale variables in South Island, New Zealand streams. *New Zealand Journal of Marine and*  
38 *Freshwater Research*, **30**, 501-523.
- 39  
40 Suren A. M. & Duncan M. J. (1999) Rolling stones and mosses: Effect of substrate stability  
41 on bryophyte communities in streams. *Journal of the North American Benthological Society*,  
42 **18**, 457-467.
- 43  
44 Thompson C. & Croke J. (2008) Channel flow competence and sediment transport in upland  
45 streams in southeast Australia. *Earth Surface Processes and Landforms*, **33**, 329-352.
- 46  
47 Townsend C. R., Scarsbrook M. R. & Doledec S. (1997) Quantifying disturbance in streams:  
48 Alternative measures of disturbance in relation to macroinvertebrate species traits and species  
49 richness. *Journal of the North American Benthological Society*, **16**, 531-544.
- 50  
51 Vericat D. & Batalla R. J. (2007) Fractional bedload transport during small floods in a  
52 regulated gravel-bed river. *Zeitschrift für Geomorphologie*, **51**, 227-240.
- 53  
54 Warburton J. & Demir T. (2000) Influence of bed material shape on sediment transport in  
55 gravel-bed rivers: A field experiment. In *Tracers in geomorphology* (ed. I. D. L. Foster), pp.  
56 401-410. Chichester: Wiley & Sons.
- 57  
58 Webb J. A., Downes B. J., Lake P. S. & Glaister A. (2006) Quantifying abrasion of stable  
59 substrata in streams: A new disturbance index for epilithic biota. *Hydrobiologia*, **559**, 443-  
60 453.

- 1  
2  
3 Westaway R. M., Lane S. N. & Hicks D. M. (2000) The development of an automated  
4 correction procedure for digital photogrammetry for the study of wide, shallow, gravel-bed  
5 rivers. *Earth Surface Processes and Landforms*, **25**, 209-226.
- 6  
7 Westaway R. M., Lane S. N. & Hicks D. M. (2001) Remote sensing of clear-water, shallow,  
8 gravel-bed rivers using digital photogrammetry. *Photogrammetric Engineering and Remote*  
9 *Sensing*, **67**, 1271-1281.
- 10  
11 Wiberg P. L. & Smith J. D. (1991) Velocity distribution and bed roughness in high-gradient  
12 streams. *Water Resources Research*, **27**, 825-838.
- 13  
14 Wilcock P. R. (1997) Entrainment, displacement and transport of tracer gravels. *Earth*  
15 *Surface Processes and Landforms*, **22**, 1125-1138.
- 16  
17 Wilcock P. R. (1996) Estimating local bed shear stress from velocity observations. *Water*  
18 *Resources Research*, **32**, 3361-3366.
- 19  
20 Wilcock P. R. (2001) Toward a practical method for estimating sediment-transport rates in  
21 gravel-bed rivers. *Earth Surface Processes and Landforms*, **26**, 1395-1408.
- 22  
23 Winterbourn M. J. & Collier K. J. (1987) Distribution of benthic invertebrates in acid, brown  
24 water streams in the South Island of New Zealand. *Hydrobiologia*, **153**, 277-286.
- 25  
26 Yalin M. S. & Karahan E. (1979) Inception of sediment transport. *Journal of the Hydraulics*  
27 *Division-Asce*, **105**, 1433-1443.
- 28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

Table 1: Methods for the assessment of shear stress (for annotations see Appendix B)

Method	Scale	Constraints	Interference with substratum	Accuracy/ Relation to biological data
Du Boys equation	reach	uniform flow, $W/h > 20$	low (measurement of parameters)	overestimation of local shear stress (Robert, 1990) but underestimation of mean shear stress (Carson & Griffiths, 1987), recommended to assess the spatial distribution of invertebrates (Statzner <i>et al.</i> , 1988)
DuBoys equation (using $h$ and $S_b$ )	patch	uniform flow	low (measurement of parameters)	underestimation of local shear stress (Lorang & Hauer, 2003)
FST-hemispheres	patch to reach, short-term	usually normal flow conditions	low	related to invertebrate distribution (Dittrich & Schmedtje, 1995; Merigoux & Doledec, 2004), negative linear relationship with invertebrate taxon richness (Merigoux & Doledec, 2004) and with mussel density (Hardison & Layzer, 2001)
Point near-bed flow velocity	patch	$h/D_{84} > 3$	low	related to invertebrate distribution (Effenberger <i>et al.</i> , 2006)
Depth averaged near-bed flow velocity	patch	simple flow geometry, logarithmic velocity profile	low	3 times more accurate than point measurement (Wilcock, 1996)
Velocity profile	patch	simple flow geometry, logarithmic velocity profile	low	profiles least accurate compared to point and depth-averaged velocity, but no knowledge of bed roughness necessary (Wilcock, 1996)

Table 2: Methods for the assessment of critical shear stress and flow competence (for annotations see Appendix B)

Method	Scale	Constraints	Interference with substratum	Accuracy/ Relation to biological data
Critical shear stress				
$\tau_{crit} \approx D$ (Lane, 1955)	reach	$h \gg D_{50}$ , $S_w < 0.01$ , uniform flow, unarmoured bed	low (measurement of D)	weak relationship with other measurers of bed stability or bryophyte cover (Death & Winterbourn, 1994; Duncan <i>et al.</i> , 1999), linked to bryophyte (Muotka & Virtanen, 1995) and invertebrate distribution (Cobb <i>et al.</i> , 1992), negative linear to number of invertebrates (Death & Winterbourn, 1995)
$\tau_{crit} = \theta_{crit} * (\gamma_s - \gamma_f) * D_i$	patch	uniform flow, uniform bed, low $h/D_i$ , low S	low (measurement of parameters)	depending on choice of $\theta_{crit}$
$\tau_{crit} = \theta_{crit} * (\gamma_s - \gamma_f) * D_{50}^c * D_i^d$	patch	uniform flow, low $h/D_i$ , low S	low (measurement of parameters)	depending on choice of c, d, $\theta_{crit}$
Combination of Shields equation and DuBoys equation (+ corrections (Duncan <i>et al.</i> , 1999))	reach	uniform flow, unarmoured bed	D, R, S	related to actual entrainment (Milan <i>et al.</i> , 2001), negative linear relationship with bryophyte cover (Duncan <i>et al.</i> , 1999), related to periphyton biomass (Biggs <i>et al.</i> , 1999)
$\tau_{crit} = a * D^b$	patch	site specific	low (measurement of D)	depending on parameters a, b
Spring balance	patch	subjectivity of particle choice	high	(Downes <i>et al.</i> , 1997)



Table 3: Methods for the assessment of erosion and deposition

Method	Scale	Constraints	Interference with substratum	Accuracy/ Relation to biological data
Scour chains	patch/ reach, event-based	substratum < boulders	intermediate during installation	related to distribution of algae (Matthaei <i>et al.</i> , 2003) and invertebrate taxa (Palmer <i>et al.</i> , 1992; Effenberger <i>et al.</i> , 2006)
Scour plates	patch, event-based	substratum < boulders	high	related to vertical invertebrate distribution (Palmer <i>et al.</i> , 1992)
Dyed sand columns/ painted gravel	patch, event-based	substratum size	high	related to vertical invertebrate distribution (Palmer <i>et al.</i> , 1992)
Pressure pillows	patch, continuous	substratum < boulders	high during installation	(Kurashige, 2002)
Morphometric budgeting	reach, event-based	gravel/ cobble substratum	low	accuracy depends on surface roughness (Brasington <i>et al.</i> , 2000)



Table 4: Methods for reach-scale tracking of tracer particles

Method	Constraints	detection depth	recovery rate	Relation to biological data and comments
Tracking of initially unembedded particles				
painted tracer (visual)	armour layer, burial	surface	15-60%	negative with periphyton biomass (Death & Zimmermann, 2005), negative linear with invertebrate species number and species richness (Death & Winterbourn, 1995; Death, 2002; Death & Zimmermann, 2005), quadratic with invertebrate taxon number ( Townsend <i>et al.</i> , 1997)
metal tracer (passive)	armour layer, particle size	0.5-1 m	50-90%	
stones wrapped in aluminium foil (passive)	armour layer	0.25 m		
magnetic tracer (passive)	armour layer, particle size	0.5-1 m, usually higher than with metal tracer	50-90%	
transmitters (active)	armour layer, particle size, battery*, low conductivity	shallow water	up to 100%	* life span: a few weeks to 10 months (size 0.01 m to 0.08 m respectively)
radioactive tracer (passive)	armour layer, environmental issues		ca. 5%	
different lithology (visual)	armour, burial	surface	5-30%	
artificial tracer (visual/passive)	armour layer, representativeness of substratum	variable	ca. 35%	
DUMPLING (active)	size (0.3 m), weight (37 kg)		100%	
Tracking of initially embedded particles				
chiselled stones (visual)	particle choice	low	low	
dyed quick concrete mix (visual)	particle choice	surface		distribution of invertebrates (Barquin & Death, 2006)

Table 5: Methods for the assessment of bedload transport

Method	Scale	Constraints	Interference with substratum	Accuracy/ Relation to biological data
pressure-difference sampler	patch, short-term	orifice area (up to 0.05 m <sup>2</sup> ), upscaling to stream width	low	sampling efficiency usually 30 – 70%, can reach up to 100%, small volume
Birkbeck slot sampler	patch/ reach	slot width, upscaling to stream width	high for installation	continuous during smaller floods
sediment trap	cross-section, continuous		high for installation	sampling efficiency up to 100%
acoustic sensors	patch/ reach	calibration	low – high for installation	comparable accuracy as bedload traps (Downing <i>et al.</i> , 2003)
ADCP	patch/ reach	sandy substratum, high suspended load	non	
electronic momentum sensor	patch	calibration	low	measures a combination of particle size and speed (Richardson <i>et al.</i> , 2003)
piezoelectric sensors	reach, long-term	calibration	low (installation)	limited accuracy for single events (Rickenmann & McArdell, 2007)
bedload transport formulae	reach	calibration site specific	low (measurement of parameters)	inaccurate for general application

Table 6: Methods for the assessment of abrasion by suspended sediments

Method	Scale	Constraints	Interference with substratum	Accuracy/ Relation to biological data
Stone blocks	patch	absolute	low	actual abrasion of sediment
Artificial blocks	patch/ months	dissolution, high bedload transport	low	only relative measurement
Abrasion coefficients	reach/ patch	calibration	none	underestimation of actual abrasion (Lewin & Brewer, 2002)

Table 7: Descriptive surveys for the estimation of bed stability on a reach-scale

Method	Constraints	Interference with substratum	Accuracy/ Relation to biological data
Pfankuch Index	subjectivity of perception	none	related to other measures of bed stability, negative linear relationship with invertebrate taxon number (Townsend <i>et al.</i> , 1997)
Pfankuch Index bottom component	subjectivity of perception	none	positively related to other measures of bed stability (Death & Winterbourn, 1994), negative linear relationship with bryophyte cover (Suren, 1996; Duncan <i>et al.</i> , 1999), negative linear relation to invertebrate species richness, number and density (Death & Winterbourn, 1995; Death, 2002)

**Appendix A: Definitions**

1		
2		
3		
4		
5		
6	Armour layer	Coarse surface layer in streams that inhibits the entrainment of
7		underlying finer material
8		
9	Bed roughness	Relief of roughness elements on the channel boundary, normally a
10		function of grain size and flow depth
11		
12	Energy gradient	Difference in potential and kinetic energy per horizontal distance
13		between two points in a stream
14		
15	Flow competence	Ability of a stream velocity to move particles of a particular size as
16		bedload
17		
18	Imbrication	Overlapping and interlocking of particles
19		
20	Incipient motion	Beginning of (grain) movement
21		
22	Laser altimetry	Approach to obtain measurements of surface elevation with laser
23		scanning techniques
24		
25	Pebble cluster	Feature developed by stream flow over alluvial beds consisting of a
26		group of particles
27		
28	Photogrammetry	Approach to obtain measurements by means of photography
29		
30	Reynolds number	Nondimensional parameter of fluid motion which determines the
31		extent to which viscosity modifies flow
32		
33	Stream power	Index for the erosive capacity of stream, defined as energy dissipation
34		per unit area, stream length or mass of water.
35		
36	Tacheometry	Survey technique that produces rapid measurements of direction,
37		elevation and distance using a kind of theodolite
38		
39	Thalweg	Deepest continuous longitudinal line along a river
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		

**Appendix B: Symbol annotation**

1		
2		
3		
4	$\tau_o$	mean boundary shear stress ( $\text{N m}^{-2}$ )
5		
6	$\tau_{\text{crit}}$	critical shear stress at incipient motion ( $\text{N m}^{-2}$ )
7		
8	$\rho_f$	density of the fluid (for pure water approx. $1000 \text{ kg m}^{-3}$ )
9	$g$	gravity acceleration ( $9.81 \text{ m s}^{-2}$ )
10		
11	$R$	Hydraulic radius ( $= A P^{-1}$ ) (m)
12		
13	$A$	cross-sectional area ( $\text{m}^2$ )
14	$P$	Wetted Perimeter at a cross-section (m)
15		
16	$S_f$	Friction slope (dimensionless)
17		
18	$S_w$	Slope of water surface ( $\text{m m}^{-1}$ )
19		
20	$S_b$	Slope of stream bed surface ( $\text{m m}^{-1}$ )
21	$h$	water depth (m)
22		
23	$D_{50}$	substratum grain size for which 50% are finer (mm)
24		
25	$D_{84}$	substratum grain size for which 84% are finer (mm)
26		
27	$D_i$	substratum grain size for which $i\%$ are finer (mm)
28	$D$	substratum grain size (mm)
29		
30	$\gamma$	specific weight ( $= \rho g$ ) ( $\text{kg m}^{-2} \text{ s}^{-2}$ )
31	$s$	sediment
32		
33	$f$	fluid
34		
35	$\theta_{\text{crit}}$	Shields coefficient or dimensionless critical shear stress
36	$v$	flow velocity ( $\text{m s}^{-1}$ )
37		
38	$W$	stream width (m)
39		
40	$Re$	Reynolds number
41	$a, b, c, d$	empirical factors in entrainment formulae
42		
43	$q_b$	bedload discharge
44		
45	$q$	water discharge ( $\text{m}^3 \text{ s}^{-1}$ )
46		
47	$q_{\text{cr}}$	critical discharge ( $\text{m}^3 \text{ s}^{-1}$ )
48	$X'$	sediment coefficient
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		